

# Washer extractor

### Features and benefits

- Compass Pro® microprocessor offers:
  - Large display and one control knob for easy program selection
  - Language selection
  - Quick selection and option buttons for the most frequently used wash programs and options
  - Wash program packages optimized on Economy, Performance and Time. (Available on general programs)

#### • AS - Automatic Savings:

- The machine weighs the linen and adjusts the amount of water and energy according to the load. This leads to considerable savings in case the machine is not fully loaded. (Available on general programs)
- Extremely low water and energy consumption see table below
- Four compartment detergent box for manual dosing of powder or liquid detergent
- · High extraction force for efficient dewatering
- Door with gasket and strong hinges built for heavy duty operation
- Stainless and galvanized steel in all vital parts for high degree of rust protection

#### PowerBalance:

- Maximises the extraction force
- Less stress on the machine
- Reduces vibrations

## Main options

- Automatic liquid detergent supply (optional I/O board)
- · Stainless steel front panel
- Connection to booking- /payment- system or coin meter
- Drain pump



Images shown are a representation of the product only and variations may occur.

Main specifications				W575H			
Max. capacity	acity filling factor 1:9		kg/lb	8/18			
Drum,	volume		litre		7	5	
	diameter		ø mm		52	20	
Extraction			rpm		12	45	
G-factor					45	50	
Standard heating alternatives electricity		kW	5.4 / 7.5				
Low energy heating alternatives electricity steam		kW	2.0 / 3.0				
		steam		X			
		non-heated				×	
Consumption data "Normal 60°C"			El		Steam***		
Economy*			Full load, 8 kg	Half load**, 4 kg	Full load, 8 kg	Half load**, 4 kg	
Total time			min	47	44	47	44
Water consumption (cold+hot)			litre	50+12	26+7	50+12	26+7
Energy consumption (motor/heating****) k\			kWh	0.15/1.1	0.15/0.7	0.15/-	0.15/-
Steam consumption			kg	-	-	1.5	0.75
Residual moisture			%	48	49	48	49
* Water temperature 15 ** Programs with AS. *** Depending on steam **** Includes hot water he							

Certified in accordance with ISO 9001 and ISO 14001 and approved IP 24D.



Electrical connections								
Heating alternative	Main voltage	Hz	Heating power kW	Total power kW	Recommended fuse A			
Electric heated	220-240V 1 ~ 220-240V 1 ~ 220-240V 3 ~ 220-240V 3 ~ 380-415V 3N ~ 380-415V 3N ~ 440V 3 ~ 480V 3 ~	50/60 50/60 50/60 50/60 50/60 50/60 60	5.4/7.5 2.0/3.0 5.4/7.5 3.0/4.3 5.4/7.5 3.0/4.3 7.5 7.5	5.5/7.6 2.1/3.1 5.5/7.6 3.1/4.5 5.5/7.6 3.1/4.5 7.6 7.6	25/35 10/16 16/20 10/16 10/16 10 16 10			
Steam or Non heated	220-480V 1/3 ~	50/60	-	1.0	10			

Water and steam connection	W575H		
Water valves Water pressure Capacity at 300 kPa Drain valve Draining capacity Steam valve Steam pressure Liquid detergent supplies	DN kPa I/min ø mm I/min DN kPa	20 200-600 20 50/75 170 15 300-600	
Floor requirements			
Frequency of the dynamic force Floor load at max extraction	Hz kN	20.8 1.9 ± 0.5	
Sound levels			
Sound power level (IEC 60704-2-4) wash extraction	dB(A) dB(A)	60 75	
Heat emission			
% of installed power, max		5	
Shipping data			
Weight Shipping volume	net, kg crated, kg m³	159 179 0.75	
Accessories			
Steel base Hose kits for water or steam Fluff collector		x x x	
Dimensions in mm			
A Width B Depth C Height D E F G H I J K L M N O		720 690 1115 355 720 825 45 1010 220 135 910 830 360 100 240	
2 Door opening ø 310 mm	Hard water Drain	at eumply	

3 Detergent box 4 Cold water


4 Cold wate5 Hot water


8 Liquid detergent supply


9 Electrical connection

10 Steam connection

Front and side panels in light grey and blue (RAL 260 70 05, 250 60 30)







<sup>\*</sup> Other voltages available, see installation manual