

Product Code: EP2/2H 12-384

EcoPro G2 2/2 Refrigerated Counter with Saladette Cut Out and Lockable Cover



Features & Benefits

- High Quality 304 Stainless Steel Exterior Build Quality
- ECA Scheme Approved as ECA products are guaranteed to be energy efficient, money can be claimed back on your investment
- Smartphone style' touch sensitive hidden until lit control pannel
- Fully floating lock provides durable security and prevents lock breakage if the key is left in
- Energy-saving Hydrocarbon refrigerant option at no extra cost
- High performance cyclopentane foam
- Airlines' ventilation system reduces compressor running time by 15%
- Take the travel out of food preparation
- Saladette dimensions 955x 510mm includes cover

External Finish 304 s/s Standard 304 S/S back for island sitting Option Worktop Standard **Base Fittings** 100mm legs in lieu of castors Option Standard **Castors 80mm** Option Legs 150mm Electrical, Service & Ecodesign Data 230/50/1 Standard **Fuse Required** 13 **Global Warming Potential** 3 **Energy Efficiency Index** 0.00 **Refrigerant Charge** 0.150

Internal Finish		
aluminium	Standard	C
Doors		A
Solid	Standard	A
Product Extras		F
Helicoil Mains Lead	Option	i Ii
		F

Shelving	
Gastronorm Pans	Option
Additional S/S Trayslides	Option
Additional GN2/1 Shelf	Option
Refrigeration	

R290 - Energy Efficient	Standard
Integral Refrigeration System	Standard
Remote Refrigeration System	Option
RH Mounted Ref Unit	Option

Specification	
Dimensions (Width)	1825
Dimensions (Height)	865
Dimensions (Depth)	800
Weight (Unpacked, kg)	145
Weight (Packed, kg)	165.87
Gross Volume	495
Noise Dba @ 1M	TBC

Footnotes

- Castors not available if product supplied less condensing unit
- 100mm leg option: height ranges from 835 to 865mm (replacement for standard castors). 150mm legs: height ranges from 885 to 935mm
- Depth with door open is 1113mm
- Decibel rating measured 1m high from the floor and 1m out from the counter
- 60Htz model supplied as 220v machine with separate transformer for conversion to 115v supply.
- Adequate airflow must be kept around the counter: 150mm











