



Product Code: EP2/3H 12-432

EcoPro G2 2/3 Refrigerated Counter with Saladette Cut Out and Lockable Cover



Features & Benefits

- High Quality 304 Stainless Steel Exterior Build Quality
- ECA Scheme Approved - as ECA products are guaranteed to be energy efficient, money can be claimed back on your investment
- Smartphone style' touch sensitive hidden until lit control pannel
- Fully floating lock provides durable security and prevents lock breakage if the key is left in
- Energy-saving Hydrocarbon refrigerant option at no extra cost
- High performance cyclopentane foam
- Airlines' ventilation system reduces compressor running time by 15%
- Take the travel out of food preparation
- Saladette dimensions 1605x 510mm includes cover

External Finish

| | |
|---------------------------------|----------|
| 304 s/s | Standard |
| 304 S/S back for island sitting | Option |
| Worktop | Standard |

Base Fittings

| | |
|-------------------------------|----------|
| 100mm legs in lieu of castors | Option |
| Castors 80mm | Standard |
| Legs 150mm | Option |

Electrical, Service & Ecodesign Data

| | |
|---------------|----------|
| 230/50/1 | Standard |
| Fuse Required | 13 |

Internal Finish

| | |
|-----------|----------|
| aluminium | Standard |
|-----------|----------|

Doors

| | |
|-------|----------|
| Solid | Standard |
|-------|----------|

Product Extras

| | |
|---------------------|--------|
| Helicoil Mains Lead | Option |
|---------------------|--------|

Shelving

| | |
|---------------------------|--------|
| Gastronorm Pans | Option |
| Additional S/S Trayslides | Option |
| Additional GN2/1 Shelf | Option |

Refrigeration

| | |
|-------------------------------|----------|
| R290 - Energy Efficient | Standard |
| Integral Refrigeration System | Standard |
| RH Mounted Ref Unit | Option |

Specification

| | |
|-----------------------|--------|
| Dimensions (Width) | 2480 |
| Dimensions (Height) | 865 |
| Dimensions (Depth) | 800 |
| Weight (Unpacked, kg) | 163 |
| Weight (Packed, kg) | 193.71 |
| Gross Volume | 760 |
| Noise DbA @ 1M | TBC |

Footnotes

- Castors not available if product supplied less condensing unit
- 100mm leg option: height ranges from 835 to 865mm (replacement for standard castors). 150mm legs: height ranges from 885 to 935mm
- Depth with door open is 1113mm
- Decibel rating measured 1m high from the floor and 1m out from the counter
- 60Hz model supplied as 220v machine with separate transformer for conversion to 115v supply.
- Adequate airflow must be kept around the counter: 150mm



Energy



Quality



Value



Design



Hygiene



After Care