



Product Code: MBCFT250W 17-167

Modular Blast Chiller with 900mm door width c/w 25mm floor and integral ramp



Features & Benefits

- MBCT models are supplied floorless for blast chilling application only
- Chilling capacity 70°C to 3°C in less than 90 minutes within specifications. Entry temperature of up to 90°C for chilling
- Freezing capacity from 70° to -18°C in less than 240 minutes within specifications
- All models supplied less condensing unit for remote application. Separate electrical supply required for condensing unit (3 phase+neutral)
- Intuitive easy touch control panel - Just press and go with easy to use colour coding to indicate cycle status.
- Foster Circularair air circulation system ensures uniform chilling whilst protecting the food surface
- Operator-friendly fans cut-out whenever door is opened
- HACCP software is available as an option in 3 formats for data retrieval and management

External Finish

White lam ext, 304 s/s door and white control panel Standard

Doors

Solid Standard

Left Hand Hinged Door Option

Product Extras

Hold Facility Option

Internal Finish

White lam Standard

Refrigeration

R404a - Industry Standard Standard

Less Condensing Unit Standard

Remote Refrigeration System Standard

Specification

Dimensions (Width) 1550

Dimensions (Height) 2350

Dimensions (Depth) 2330

Weight (Unpacked, kg) 790

Weight (Packed, kg) 790

Chilling Capacity (Kgs) 250

Gross Volume 250

RS485 connection for HACCP data logging Option

Noise DbA @ 1M TBC

Shelving

Additional S/S Trayslides Standard

Trolley - Gastronorm - 1/1 (Not Supplied) Option

Trolley - Gastronorm - 2/1 (Not Supplied) Option

Trolley Capacity - 890x1040x1890 Standard

Electrical, Service & Ecodesign Data

400/50/3 Standard

Footnotes

- MBC models are supplied floorless for blast chilling application only.
- Control panel sprayed white
- Capacity 75kg. Chilling capacity 70oC to 3oC in less than 90 minutes within specifications. Entry temperature or up to 90oC for chilling.
- Anti Condensation heater to control panel recommended where products are installed in an ambient below 15oC e.g. Prep rooms
- Condensing Unit: All models supplied less condensing unit for remote application. Separate electrical supply required for condensing unit (3 phase + neutral).



Energy



Quality



Value



Design



Hygiene



After Care