



Product Code: MBCFT250W 17-168

Modular Blast Chiller with 900mm door width c/w 25mm floor and integral ramp



Features & Benefits

- MBCT models are supplied floorless for blast chilling application only
- Chilling capacity 70°C to 3°C in less than 90 minutes within specifications. Entry temperature of up to 90°C for chilling
- Freezing capacity from 70° to -18°C in less than 240 minutes within specifications
- All models supplied less condensing unit for remote application. Separate electrical supply required for condensing unit (3 phase+neutral)
- Intuitive easy touch control panel - Just press and go with easy to use colour coding to indicate cycle status.
- Foster Circulair air circulation system ensures uniform chilling whilst protecting the food surface
- Operator-friendly fans cut-out whenever door is opened
- HACCP software is available as an option in 3 formats for data retrieval and management

External Finish		Internal Finish		Shelving	
304 s/s ext	Standard	304 s/s	Standard	Additional S/S Trayslides	Standard
Doors		Refrigeration		Trolley - Gastronorm - 1/1 (Not Supplied)	Option
Solid	Standard	R404a - Industry Standard	Standard	Trolley - Gastronorm - 2/1 (Not Supplied)	Option
Left Hand Hinged Door	Option	Less Condensing Unit	Standard	Trolley Capacity - 890x1040x1890	Standard
Product Extras		Remote Refrigeration System	Standard	Electrical, Service & Ecodesign Data	
Hold Facility	Option	Specification		400/50/3	Standard
		Width	1550		
		Height	2350		
		Depth	2330		
		Weight (Unpacked, kg)	790		
		Weight (Packed, kg)	790		
		Chilling Capacity (Kgs)	250		
		Gross Volume	250		
		RS485 connection for HACCP data logging	Option		
		Noise dBA @ 1m	TBC		

Footnotes

- MBC models are supplied floorless for blast chilling application only.
- Control panel sprayed white
- Capacity 75kg. Chilling capacity 70oC to 3oC in less than 90 minutes within specifications. Entry temperature or up to 90oC for chilling.
- Anti Condensation heater to control panel recommended where products are installed in an ambient below 15oC e.g. Prep rooms
- Condensing Unit: All models supplied less condensing unit for remote application. Separate electrical supply required for condensing unit (3 phase + neutral).



Energy



Quality



Value



Design



Hygiene



After Care