



Electrolux

High Productivity Cooking Variomix Electric Boiling Pan with Stirrer 50lt, 600mm tilting height

ITEM # _____

MODEL # _____

NAME # _____

SIS # _____

AIA # _____



Electrolux

Variomix Electric Boiling Pan with Stirrer 50lt, 600mm tilting height

High Productivity Cooking



232223 (SM6V50)

Electric boiling pan 50lt with stirrer, with 600mm tilting height

Short Form Specification

Item No.

AISI 304 stainless steel construction; deep drawn pan with rounded edges manufactured from AISI 316 stainless steel. Pan can be tilted beyond 90° to completely empty the food. Motorised tilting with tilting axis located at the front of the pan to keep the pouring lip high and allow tall vessels to be filled. Food is uniformly heated via the base and the side walls of the pan by an indirect heating system using integrally generated saturated steam at a temperature of 120°C in a jacket with an automatic deaeration system. Safety valve avoids overpressure of the steam in the jacket. Safety thermostat protects against low water level. Max pressure at 1,5 bar. Programmable water filling system. Bottom agitator mixes at speeds from 25 to 100 rpm. Whipping cycle up to 200 rpm. Continuous rotating or 2 rotating directions with the possibility to modify times. Step program facilitates removal of food. High thermal input and fast heat up. Electronic SMART control with possibility to store 50 programs; error message facility; display with: cooking time and temperature, water filling. Heavy duty balanced stainless steel lid, easy to remove and turn to facilitate cleaning. The insulation allows a lower temperature on the outer panels. The foamed thermal insulation guarantees a cool upper edge of the cooking vessel surface. IPX5 water protection. For freestanding installation one left column is necessary for each unit. 600mm tilting height.

Main Features

- Curved pan base guarantees that the appliance is also suitable to prepare small quantities of food.
- Safety valve avoids overpressure of the steam in the jacket.
- Safety thermostat protects against low water level.
- High-quality thermal insulation of the pan saves energy and keeps operating ambient temperature low.
- Compliant to CE requirements for safety.
- Constructed to meet the highest hygiene standards.
- Fast working thanks to the high efficient heating technology and well insulation that keeps the heat inside the well.
- High thermal input and fast heat up.
- Isolated upper well rim avoids risk of harm for the user.
- Electronic control with possibility to store up to 50 programs, large display for easy use and a complete control over the following functions: start, cooking time, temperature, water filling and mixing speed.
- Food is uniformly heated through the base and side walls of the pan by an indirect heating system which uses integrally generated saturated steam at a temperature of 120°C in a jacket with an automatic deaeration system.
- OPTIONS (to be ordered with the machine and must be installed in the factory):
 - Automatic water filling - makes it possible to preset the desired quantity of water
 - Automatic cooling - allows cooling down of the food connecting the jacket to the tap network
 - Food sensor - placed on the bottom of the vessel, it provides efficient temperature control even with small amounts of food. Can be connected to HACCP integrated system
 - Spray gun - integrated spray unit
- ACCESSORIES:
 - Whipping tool - quickly whips foods such as cream, egg whites, etc
 - Bottom agitator - blends foods such as meat stews, casseroles, etc
 - Cleaning tool - may be fitted on the rotating shaft to facilitate cleaning of the cooking surface and safety grid. After use, it may be placed directly in the dishwasher and the brushes may be replaced
- 600 mm tilting height minimum.

Construction

- Tilting axis located at the front and upper position of the pan to keep the pouring path short when filling different types of vessels.
- AISI 304 stainless steel construction with AISI 304L stainless steel deep drawn pan with rounded edges.
- Vessel can be tilted beyond 90° to completely empty the food.
- Motorised tilting.
- Ergonomic and user friendly thanks to the high tilting position and the pouring lip design which

APPROVAL: _____

allow to easily fill containers.

- Max pressure 1,5 bar.
- Heavy duty, balanced stainless steel lid with sliding plastic cover to insert ingredients. Easy to remove and turn to facilitate cleaning.

Included Accessories

- 1 of GRID STIRRER W/SCRAPERS FOR 50L PNC 928050

Optional Accessories


- STRAINER 50L PNC 928024
- Kit for a correct and easy positioning and installation of 50-100 lt pan (for a correct installation you need 2 for each pan) PNC 928029
- FOUNDATION FRAME LEFT COLUMN PNC 928031
- FOUNDATION FRAME RIGHT COLUMN 50-100L PNC 928032
- FASTENING FRAME LEFT COLUMN(FOR BOLTING) PNC 928034
- FASTENING FRAME RIGHT COLUMN 50-100L PNC 928035
- TROLLEY TO STORE TOOLS FOR 5 BOIL. PANS PNC 928043
- TROLLEY TO STORE TOOLS FOR 2 BOIL. PANS PNC 928044
- DISTANCE RING F.CONNECT.(PREV. VERS.PAN) PNC 928049
- SET OF SCRAPERS F.GRID STIRRER 50L PNC 928056
- PROPELLER STIRRER F.50L-ALL VERSIONS PNC 928061
- WHIPPING TOOL FOR 50L PNC 928071
- BRUSH (SHORT) FOR SPRAY UNIT PNC 928082
- BRUSH (LONG) FOR SPRAY UNIT PNC 928083
- OPTION FOOD TEMPERATURE+HACCP 50/150 LT PNC 928100
- OPTION AUTOMATIC WATER FILLING PNC 928102
- Cleaning tool for Variomix boiling pans, 50lt PNC 928119
- OPTION AUTOMATIC COOLING 50 LT PNC 928129
- Level control for 50lt boiling pan without jacket cooling PNC 928139
- Level control for 50lt boiling pan with jacket cooling PNC 928144
- STEAM KIT BOIL.PAN,LFT COLMN600MM TILT H PNC 928150
- Right column including with bearing and cover for boiling pans, with 400mm tilting height PNC 928151
- Automatic ice cooling system for electrical heated smart boiling pan 50lt with 600mm tilting height PNC 928153
- - NOT TRANSLATED - PNC 928161
- - NOT TRANSLATED - PNC 928162
- - NOT TRANSLATED - PNC 928167




Electrolux

High Productivity Cooking Variomix Electric Boiling Pan with Stirrer 50lt, 600mm tilting height

Front




Side



- CWI = Cold Water inlet
- EI = Electrical connection
- HWI = Hot water inlet

Top



Electric

Supply voltage:

232223 (SM6V50) 400 V/3N ph/50 Hz

Electrical power, max:

16 kW

Installation

Distance back floor tilted: 638 mm

Key Information

Working Temperature MIN: 30 °C

Working Temperature MAX: 121 °C

Vessel (round) diameter: 425 mm

Vessel (round) depth: 425 mm

External dimensions, Width: 990 mm

External dimensions, Height: 1050 mm

External dimensions, Depth: 915 mm

Net vessel useful capacity: 50 lt

Tilting mechanism: Automatic

Bearing: Front

High Productivity Cooking Variomix Electric Boiling Pan with Stirrer 50lt, 600mm tilting height

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

