

www.burco.co.uk



## **BURCO 20L TWIN TAP COUNTERTOP AUTO FILL** WATER BOILER - With Filtration







- $\checkmark$ Easy-to-replace internal filtration system Inhibits limescale build-up and other impurities to prolong the life of the appliance and provide the best tasting beverage.
- Extra Large 20L tank capacity & 2 independently controlled taps

Ideal for high traffic areas and premises requiring a large volume of instant hot water.

- Manufactured in the UK
- Advanced LCD touch control screen Provides great user functionality and the advanced diagnostics alert the user when the filter cartridge needs to be replaced.
- Variable water temperature range Simply select your preferred setting between 80°C and 98°C.
- **Energy saving "Eco" Mode** Reduces running costs.
- **Powerful 6kW heating element** For rapid heat-up time.
- Hard-wiring required
- **WRAS Approved**



## SKU CODE: **PRODUCT CODE: DESCRIPTION:** 444442465 BC PLS AF CT 20L TT 6KW UK

Burco 20L Twin Tap Countertop Auto Fill Water Boiler – with filtration

## www.burco.co.uk





## FULL SPECIFICATION - Burco 20L Twin Tap Countertop Auto Fill Water Boiler – with filtration

SKU code	44442465
GDPA code	BC PLS AF CT 20L TT 6KW UK
EAN code	5052263024656
Туре	Countertop
Capacity (L)	20
Unit dimensions (W x D x H) (mm)	344 x 464 x 689 (depth includes taps & drip tray)
Packed dimensions (W x D x H) (mm)	450 x 550 x 760
Product weight (kg)	11.7
Packed weight (kg)	14.73
Body construction	430 grade Stainless Steel
Tank construction	304 grade Stainless Steel
Drip tray size (W x D x H) (mm)	345 x 220 x 92
Trim & drip tray plastic type	ABS
Power rating (kW)	6
Water delivery temperature	80°C - 98°C
Typical Heating and Cooling times	Heat up time to 98° C: 34 minutes
	Heat from 80-98° C: 7 minutes
	Cool down from 98°C-80°C: 167 minutes
Output per hour	Litres: 60
	<b>Pints:</b> 106
	Cups: 399
Tap height	220mm from drip tray ( <mark>tbc</mark> )
Inline water filter	Yes
Replaceable water filter	Yes
Water inlet connection fitting	34″ BSP
Water feed hose length (Supplied) (m)	2
Max Water inlet pressure (bar)	10
Voltage supply	220-240V 50-60Hz
Single phase hardwiring required	Yes
Electrical Supply 1N~+E current (A)	26
Electrical Supply 3N~+E current (A)	L1 - 13, L2 - 13, L3 - NA
Plug type	N/A Hard Wired
Fitted cable length (m)	N/A Hard Wired
None slip feet for safety	Yes
Boil dry thermal cut out	Yes
Country of manufacture	UK
Tariff code	8516101100
WRAS approved	Yes
Warranty	Up to 2 years Parts & Labour