

INSTALLATION & CARE INSTRUCTIONS

TAP PRODUCTS

CATERTAP
manufactured by **MECHLINE**

Thank you for purchasing your CaterTap product.

GENERAL ADVICE



Please follow these instructions carefully to ensure trouble free operation.

- Inspect the product for damage carefully before installation. No claims for damage can be accepted after installation.
- Ensure all pipework is flushed free of debris before installation.
- Always fit a service valve to the hot & cold supplies.
- If flexible hoses are used, ensure they are not kinked, twisted or crushed during installation.
- Ensure supply pipes are properly sized to avoid problems with flow rate, pressure loss or water hammer.
- Protect the installation with water filters, water-hammer arrestors, and water pressure reducers as required.
- Do not install the products where there is the possibility of the water supplies freezing.
- Only connect twin feed models to water supplies with reasonably balanced pressures within 1 Bar. Maximum recommended water temperature 60°C. Recommended minimum water pressure 1.5 Bar. Maximum water pressure 10 Bar. Recommended dynamic water pressure 1.5-3 Bar.
- 1/2-inch connections for all models.
- Recommended tap hole diameter is 25mm for all models.
- Tap hole centres for deck mixer models: 180mm



- Recommended cleaning of chrome-finished products: Do not use abrasive, chlorine or acid-based cleaning products. Avoid contact with concentrated bleach. Clean with soapy water using a cloth or sponge.

MECHLINE DEVELOPMENTS LIMITED

Tel: +44 (0)1908 261511 | Email: info@mechline.com | Web: www.mechline.com