

ADVANCE 50 FTWH70LS4 U

1 door undercounter freezer



ACCESSORIES INCLUDED

2 white shelves

OPTIONAL EXTRAS

1120782 – GN Rail RT UC-70

1120783 – GN Rail LT UC-70

PRODUCT SERIES: ADVANCE 50

ITEM NUMBER: WHU81110002

COUNTRY OF ORIGIN: INDIA

Hoshizaki ADVANCE 50 FTWH70LS4 U is an undercounter freezer with right hand hinged door and integrated handle. It has a net usable volume of 79.7ltr. Castors H = 125mm and shelf width is 530mm.

- Fan-assisted cooling
- Air duct inside for guided airflow
- Air duct at rear side for guided hot airflow
- Automatic fan cut-out when door is opened
- Automatic defrost with re-evaporation of defrost water
- Electronic controller with temperature indicator
- Climate class 5 cooling system enduring up to +40°C ambient temperature
- Self-closing and reversible door
- Wide opening angle for easy loading of cabinet
- Door with integrated handle and lock
- Replaceable magnetic door gasket
- Adjustable shelf supports in increment of 25.4mm/1 inch
- Internal LED light
- Castors height 125mm
- Pan-shaped inside base with rounded corners to catch fluids
- Ideal for side-by-side positioning

GN Pan capacity:

- GN 1/1 65mm deep: 5 pc
- GN 1/1 100mm deep: 4 pc
- GN 1/1 150mm deep: 3 pc

WARRANTY PERIOD

5 Years on Parts & Labour

EXTERIOR

Stainless Steel AISI 430

INTERIOR

Stainless steel

Refrigerant type: R290 / Refrigerant: 0.055 kg / CO2 equivalent: 0.165 kg

Energy consumption	Energy efficiency class	Energy efficiency class standard	Energy Efficiency Index (EEI)
983 kWh/year	B	ISO 22041: 2019	34.54 EEI

CERTIFICATIONS



ADVANCE 50 FTWH70LS4 U

TECHNICAL SPECIFICATIONS

Temperature range	GN tray size	Shelf size	Volume, gross	Net usable volume	Climate class	Sound level
-23/-7°C	1/1 GN	W 530 x D 300 mm	169 l	79.7 l	5 (max. ambient 40°C w/ 40% RH)	45.7 dB(A)

Power supply	Connection load	Ref. capacity (at -30°C)
230V, 1N-/50 Hz	220 W	218 W

SHIPPING SPECIFICATIONS

Width (packed)	Depth (packed)	Height (packed)	Volume (packed)	Gross weight	Width	Depth	Height	Net weight
777 mm	856 mm	883 mm	0.587 m3	82 kg	700 mm	785 mm	825 mm	67 kg

Disclaimer: Every effort has been made to ensure that the information contained in this spec sheet is accurate at the time of publishing. Hoshizaki Europe BV assumes no responsibility or liability for typographical errors or omissions or for any misinterpretation of the information within the publication and reserves the right to change without notice.

