

Blast Chillers CW Blast Chiller Crosswise 56kg (R452A)

ITEM # _____

MODEL # _____

NAME # _____

SIS # _____

AIA # _____


727892 (RBC20156)

 Blast chiller 56kg,
 compatible with 20x1/1 GN
 crosswise oven - R452A

Short Form Specification

Item No. _____

For 20 GN1/1 or 600x400 mm trays. Load capacity: chilling 56 kg; (UK guidelines). Main components in 304 AISI stainless steel. Internal rounded corners and drain. Built-in refrigeration unit. Automatic detection of food probe insertion. Automatic and Manual defrost. Blast chilling real residual time estimation (A.R. T.E.). Turbo cooling function. Specific cycles for ice cream. Evaporator with antirust protection. Digital temperature and time display. HACCP and Service alarms with data logging. Operating air temperature: +3 -12°C. For ambient temperatures up to 40°C. Cyclopentane insulation (HCFC, CFC and HFC free). R452A refrigerant gas (HCFC and CFC free).

Main Features

- Soft Chilling (air temperature -2°C).
- Hard Chilling (air temperature -12°C).
- Holding at 3°C for chilling, automatically activated at the end of each cycle, to save energy and maintain the target temperature (manual activation is also possible).
- Turbo cooling: chiller works continuously at the desired temperature; ideal for continuous production.
- Control unit provides two large displays to read out: time, core temperature, cycle countdown, alarms, service information.
- Two customizable cycles (P1 & P2) for each operating mode, allowing to set the time and air temperature. These programs can be converted into ice-cream specialized cycles (shape maintenance and holding).
- All information related to the different operating models are recorded: date, time, cycle, core temperature, holding temperature, HACCP accordance.
- Single sensor core probe as standard.
- Remaining time estimation for probe-driven cycles based on artificial intelligence techniques (ARTE) for an easier planning of the activities.
- Performance guaranteed at ambient temperatures of +40°C.
- Blast Chilling cycle: 56 kg from 90°C up to 3°C in less than 90 minutes.

Construction

- High density polyurethane insulation, 60 mm thickness, HCFC free.
- Ventilator swinging hinged panel for access to the evaporator for cleaning.
- No water connections required.
- Waste water can be plumbed into drain, but can also be collected in an optional waste container.
- Environmentally friendly: R452a as refrigerant gas.

APPROVAL: _____


Included Accessories

- 1 of 1 single-sensor probe for blast chiller PNC 880213 and blast chiller&freezers
- 1 of Removable tray support rack for 20 GN 1/1 PNC 881010


Optional Accessories

- Kit for HACCP advanced connection for LW and CW blast chiller&freezer PNC 880183
- 3-sensor probe for blast chiller and blast chiller/freezers PNC 880212
- 1 single-sensor probe for blast chiller and blast chiller&freezers PNC 880213
- Rilsan grid 600x400mm PNC 880864
- Removable tray support rack for 20 GN 1/1 PNC 881010
- Plastic coated grid, 1/1GN PNC 881061
- Rack rails for vertical blast chiller and blast chiller&freezer PNC 881182
- Pair of 1/1GN AISI 304 stainless steel grids PNC 921101
- Trolley for 20x1/1GN roll-in rack PNC 922132
- Kit HACCP EKIS PNC 922166
- 60mm pitch roll-in rack for 20x1/1GN (included with the oven) PNC 922203
- 80mm pitch roll-in rack for 20x1/1GN PNC 922205

Front




Side



EI = Electrical inlet (power)
 RO = Refrigerant Outlet

Top



Electric

Supply voltage:
 727892 (RBC20156) 380-415 V/3N ph/50 Hz
Electrical power max.: 2.45 kW
Circuit breaker required

Installation:

Clearance: 5 cm on sides and back.
 Please see and follow detailed installation instructions provided with the unit

Capacity:

GN: 6 - 1/1 containers

Key Information:

External dimensions, Width: 800 mm
External dimensions, Height: 2230 mm
External dimensions, Depth: 835 mm
Net weight: 231 kg
Shipping weight: 261 kg
Shipping volume: 1.83 m³

Refrigeration Data

Refrigerant type: R452A
Refrigeration power: 5363 W
Refrigeration power at evaporation temperature: -5 °C
Refrigerant weight: 2400 g

Product Information (Commission Regulation EU 2015/1095)

Energy consumption, cycle (chilling): 0.067 kWh/kg
Chilling Cycle Time (+65°C to +10°C): 119 min
Full load capacity (chilling): 65 kg