



# Electrolux

## Accessories Pre-wash Spray Unit with Single Hole

ITEM # \_\_\_\_\_

MODEL # \_\_\_\_\_

NAME # \_\_\_\_\_

SIS # \_\_\_\_\_

AIA # \_\_\_\_\_



# Electrolux



Accessories

Pre-wash Spray Unit with Single Hole

855315 (DWAC04)

Prewash spray unit, single hole

### Main Features

- Heat-insulating and limescale-resistant thermoplastic components.
- Water flow: 16 l/min with 3 bar.
- All pre-rinse unit are equipped with check valves in compliance with EN 1717.
- Mounting hole: 29mm.

### Construction

- Support spring in harmonic steel.
- Flexible hose in EPDM rubber, certified for portable water; reinforced with stainless steel double braid and transparent thermoplastic coating.
- The spray gun allows a progressive water flow with internal components in stainless steel and EPDM rubber certified for food.
- Knobs made in chromium-plated high quality tecnopolymer that is resistant to temperature of up to 90°C. High flow and high durability stem valves.
- Faucet body made in hard chromium-plated brass, massive heavy-duty construction and it is resistant to temperature up to 90°C. Monting shank: G3/4", 50mm long and ring nut for maximum stability and ease of installation.
- Idraulic connection MG 1/2 male-threaded compression coupling.
- Stainless steel spray gun bracket with fiberglass body.
- 150mm long wall bracket in fiberglass.
- Riser pipe in AISI 316 stainless steel.

APPROVAL: \_\_\_\_\_

