

Tumble dryer

TD6-17S



Exceptional savings and effortless use



Priority on people

Certified ergonomic design with a human-centered approach for an outstanding user experience

- Lint filter
The horizontal filter drawer is positioned for easy access and cleaning without the need to bend down
- Large door opening for easy loading and unloading
- Easy access to vital parts from front and rear for simple servicing
- Simple use operational panels with selection of temperature and time for easy operation and selection



Long-term savings

Innovative features to save money and time, and embrace a sustainable lifestyle with excellent water evaporation efficiency per kWh

- Moisture Balance (optional) helps to stop the drying process at the right time to save on energy costs
- The coin version with Ecopower to avoid over drying of the garments and get a lower energy consumption



Pure control

Monitor your equipment and performance from anywhere, allowing to take action and to improve your business with OnE Laundry - the personal assistant for hygiene validation management, process management and revenue management (optional)



Outstanding productivity

Dry more laundry in less time: a game-changing improvement

- Reversing drum minimizes wrinkles and drying time to get an effective and even drying performance with 2 full loads per hour per pocket



Global Advanced Hygiene

Global Advanced Hygiene program package¹ with proven log 6 reduction^{II} disinfection of textiles through the laundry process, fulfilling the criteria of all local approved standards

I. program is available in the standard library of gas and electric heated dryers, excluding products for specific segments where temperature is not controllable

II. log 6 reduction equals to 99,9999% viral infectivity reduction. The efficacy of reduction of SARS-CoV-2 and other pathogens in the process is confirmed by RISE (The Research Institute of Sweden) on the basis of Electrolux Professional laboratory data



Images shown are a representation of the product only and variations may occur.

Other options

- Payment: coinmeter with Ecopower
The coin version with Ecopower to avoid over drying of the garments and get a lower energy consumption
- Stainless steel drum, Stainless steel front
- High altitude kit for gas heated tumble dryers

Main specifications ¹		TD6-17S			
Rated capacity, filling factor 1:18	kg / lb	16.7 / 37			
Rated capacity, filling factor 1:22	kg / lb	13.6 / 30			
Drum, volume	litre	300			
Drum, diameter	ø mm	760			
Heating alternatives:					
Gas	kW / BTU/h	21 / 71700			
EI	kW	9.0 / 13.5 / 18.0			
Consumption data²		Gas	EI 9.0 kW	EI 13.5 kW	EI 18.0 kW
Total time	Min	21	43	29	24
Energy consumption	kWh	7.11	6.65	6.51	6.51
Evaporation	g/min	329	160	231	279
Energy water evaporation	kWh/l	1.03	0.96	0.97	0.97

1. Value per pocket.

2. At rated capacity 1:22, 100% cotton load at 50% initial moisture dried to 0%.

Electrical connections					
Heating alternative	Main voltage	Hz	Heating power kW	Total power kW	Recommended fuse A
Electric heated ¹	220-240V 3-	50/60	9.0	10.0	25
	380-415V 3N/3-	50/60	9.0/13.5/18.0	10.0/14.5/19.0	16/25/32
	440V 3-	60	9.0/13.5/18.0	10.0/14.5/19.0	16/20/25
	480V 3-	60	9.0/13.5/18.0	10.0/14.5/19.0	16/20/25
Gas heated ¹	220-480V 1/1N/3/3N-	50/60	³	1.0	10
Gas heated ²	220-480V 1/1N/3/3N-	50/60	³	2.0	10

1. Per pocket.
2. Complete machine.
3. Total power and recommended fuse does not depend on the heating power in those cases.

Gas and air connections ¹		TD6-17S
Gas	ISO 7/1-R1	1/2"
Gas pressure, Natural gas	Pa	2000
	mbar	20
Gas pressure, Propane	Pa	2800-5000
	mbar	28-50
Air outlet	ø mm	200
Evacuated air, gas/el	m ³ /h	600 / 600
Pressure drop, gas/el	Max. Pa	400 / 400

Sound levels	
Sound power/pressure level at drying ²	dB(A) 76/60

Heat emission	
% of installed power, max	15

Shipping data ³	
Weight	net, kg 289
Shipping volume	m ³ 2.03

1. Operating panel
2. Door opening, ø 580 mm
3. Electrical connection
4. Gas connection
5. Exhaust connection

1. The default gas appliances are built to run on either GNH or LPG gas where shall be installed at not over than 610 m (2001 ft) high altitude otherwise a kit for high altitude must be installed to the machine. For the kit No. please refer to the spare parts list.
2. Sound power levels measured according to ISO 60704.
3. Average data. Crated weight/shipping volume depends on configuration. Please contact logistics for exact measures.

