

# DISHWASHER AX-51BCD 230/50/1

Commercial glass- and dishwasher. Rack size 500x500mm and door clearance 380 mm.

# SALES DESCRIPTION

Sani-Control: guaranteed disinfection. Constant high temperatura rinse system for optimal disinfection. Embedded bodywork and easy-grip door: hygienic and ergonomic.

Exclusive Hydroblade<sup>™</sup> washing arms: maximum effectiveness.

3-stage filtering system.

Double-walled body (partial).

Multi-power model. Default boiler loading: 2000W.

### Sani-Control guarantee

- GUARANTEED DISINFECTION in compliance with standard DIN 10534.
- THERMAL LOCK function: Ensures that rinsing will be carried out at the ideal temperature to disinfect the dishes.
- CONSTANT HIGH TEMPERATURE RINSE system for optimal disinfection.
- ✓ The PRESSURE PUMP guarantees effective high-pressure rinsing
- WRAS certified.

#### New recessed bodywork

- Ergonomic design with rounded corners to prevent the accumulation of dirt and facilitate cleaning.
- Compact tank volume (50% water saving compared to the previous range).
- Embedded basket guides

#### Hydroblade<sup>™</sup> washing arms

- Redesigned nozzles for greater washing performance.
- The "monoblock" design delivers durability and resistance to impacts.
- ✓ 30% savings in water consumption during rinsing compared to the previous range.

#### 3-stage filter system: surface, tank and extraction



- Keeps the washing water in optimal conditions to maintain constant washing performance.
- The surface filters feature an "easy-on" design and can be quickly removed without having to disconnect the washing arms.

#### "Easy grip" door: new design with integrated door handle

- ✓ The integration of the components provides greater resistance and robustness.
- $\checkmark$  Designed to have no corners or areas that are difficult to access: prevents deposits of dirt and facilitates cleaning.
- $\checkmark$  Its ergonomic handle provides a perfect grip, even with wet hands.
- ✓ Double-walled door with safety microswitch and high quality seal
- 38 cm loading capacity: high versatility for washing a wide range of items: dishes, Euronorm trays, GN 1/1 tubs and pizza plates diam 39

#### Warewashing, made simple

- ✓ Active Xperience: simple and intuitive use
- Dedicated cycles: selection of the ideal washing programme using icons.
- Electronic control panel with IP65 humidity protection.

#### You will never WASH ALONE

- ✓ Tech-Services: our team of technicians will help you so that your machine is always ready for use.
- ✓ Design Services: tell us what your needs are and we will advise you.
- ✓ 60 years of experience and know-how at your disposal.

## **NCLUDES**

- ✓ Peristaltic Detergent Pump.
- ✓ Rinse aid pump.
- 1 glasses basket.
- Overflow drainage pump. Tank water renewal by the principle of density.
- ved break tank.

Type-A air break. WRAS appro-

- 1 mixed basket (plates).
  - 1 small basket for cutlery.
- Optional

softener.

Automatic built-in water

Double-level accessory for washing two baskets at the same time.

# ACCESSORIES

- Manual water softeners
- Automatic water softeners
- □ 500 x 500 mm. baskets

#### □ Inserts & supplements High feet kit

- - Double rack kits for AX/UX

# **SPECIFICATIONS**

Basket dimensions: 500 mm x 500 mm Useful height: 380 mm

Cycle duration: -- " / -- " / -- " Production baskets/hour: 30 / 24 / 17

Wash temperature: 50 °C - 65 °C Rinse temperature: 65 °C - 87 °C

- ✓ Boiler capacity: 8 I
- ✓ Wash tank capacity: 14 I
- ✓ Water consumption/cycle: 2.5 I

#### Loading

Pump: 500 W / 0.7 Hp Tank: 1800 W Boiler: 5000 W Total loading: 5500 W

Electrical supply: 230 V / 50 Hz / 1 ~ (25 A)



Commercial glass- and dishwasher. Rack size 500x500mm and door clearance 380 mm.

ςρ

### External dimensions (WxDxH)


√ Width:580 mm

- ✓ Depth: 635 mm
- ✓ Height: 835 mm

Net weight: 70 Kg

Noise level (1m.): <70 dB(A)

**Crated dimensions** 640 x 695 x 960 mm Gross weight: 77 Kg





www.sammic.co.uk Food Service Equipment Manufacturer Unit 2, Trevanth Road Troon Industrial Park LE4 9LS - Leicester

uksales@sammic.com Tel.: +44 0116 246 1900



Project Date Item Qty Approved

updated 29/05/2023 product sheet