

t3

Advanced hot tap
technology for superior,
sustainable hot & chilled
drinks.



Overview

- Intelligent hot tap technology.
- Premium aesthetic.
- Powerful and energy-efficient.
- Intelligent energy-efficiency
- Hygiene assurance in every pour.
- Bluetooth® touchless water dispensing

Specifications

- Chilled temperature - 2°C
- Hot temperature - 92°C
- ProCore+ flow rate - 80L/h
- ProCore flow rate - 50L/h
- Hot flow rate - 16L/h

Accessories

- [500ml water bottles](#)
- [Printed paper cups 463428](#)
- [Install kit with 3M filter 461202](#)
- [Refill station cabinet 601604](#)

T3 ProCore W320xD471xH400mm - Includes the Simple-fit Ventilation Base

Dispense Options	Water system	Max power consumption	Black	Steel	Black LED-UV	Steel LED-UV
Chilled, Ambient & Hot	Dry Chill®	1670W	Z43160	Z43170	Z43180	Z43190
Chilled, Sparkling, Ambient & Hot	Dry Chill®	1670W	Z43240	Z43250	Z43260	Z43270

T3 ProCore+ W320xD471xH400mm - Includes the Simple-fit Ventilation Base

Dispense Options	Water system	Max power consumption	Black	Steel	Black LED-UV	Steel LED-UV
Chilled, Ambient & Hot	Dry Chill®	1710W	Z43480	Z43490	Z43500	Z43510
Chilled, Sparkling, Ambient & Hot	Dry Chill®	1710W	Z43560	Z43570	Z43580	Z43590

borg &
overström

Find out more:

<https://www.borgandoverstrom.com/en/p/tap-systems/t3/>