



## EFFICIEN-C SINGLE DOOR BOTTLE COOLER HINGED 150L BLACK



- ✓ **Temperature range of +2° C to +10° C**  
Ideal for storing a variety of drinks and wine at preferred temperature
- ✓ **Forced air cooling**  
Enables faster temperature recovery after door opening or restocking
- ✓ **R600a refrigerant**  
Environmentally friendly refrigerant
- ✓ **Double glazed safety glass**  
Designed to withstand the demands of a busy back bar area
- ✓ **Self-closing doors**  
Maximises energy efficiency to keep stock cool
- ✓ **Removable and replaceable door seal**  
For easy cleaning and increased product life-span
- ✓ **2 adjustable shelves**  
For added versatility for bottles and cans of different sizes
- ✓ **External temperature display**  
No need to open the door to check the temperature
- ✓ **LED Internal light**  
Shows contents more effectively with a simple on/off switch
- ✓ **Lockable**  
For security of contents

SKU CODE:      PRODUCT CODE:      DESCRIPTION:

444443190      BC6097K LED      EfficienC Single Door Bottle Cooler Hinged 150L Black LED



## FULL SPECIFICATION – BC6097K LED EfficienC Single Door Bottle Cooler Hinged 150L Black



SKU code	444443190
EAN code	<b>5052263031906</b>
GDPA code	BC6097K LED
Number of doors	1
Door opening type	Hinged
Colour	Black
Product dimensions (mm) (WxDxH)	600x500x900
Packed dimensions (mm) (WxDxH)	640x580x950
Product weight (kg)	48
Packed weight (kg)	55
Material – exterior finish	Black painted steel
Material – interior finish	Stainless steel
Gross capacity (L)	150
Capacity (330ml bottles)	106
Capacity (330ml cans)	154
Internal dimensions (WxDxH)	520x385x750
Internal temperature Range	+2° C to +10° C
Maximum ambient operating temperature	Up to +38° C
Defrost type	Automatic
Forced air cooling (fan)	Yes
Self closing door(s)	Yes
Door open depth (mm)	1090
Replacement door seal	Yes
Controller type	Electronic
External temperature type	Yes
Number of shelves	2
Shelf size (mm) (WxD)	500x345
Shelf material	Chrome finish wire shelves
Front adjustable feet	Yes
LED Interior light	Yes
Light activation	Switch on exterior
Fitted lock	Yes
Insulation thickness (mm)	40
Insulation material	Pentane
Voltage supply (V)	220/240
UK 3 pin plug	Yes
Fitted cable length (m)	1.5
Refrigerant type	R600a
CFC free	Yes
HFC free	Yes
HCFE free	Yes
Ammonia free	Yes