

Equajet 20 level GN 1/1 electric oven

Ref. BEJE201-1-11

EQUAJET THE ESSENTIALS

Intelligent cooking®:

CoreControl: power is adjusted to suit the load
Immediate temperature adjustment
JetControl: advanced injection technology
Rapid cooling of the oven cavity

VisioPAD:

Touch control panel, Clear, intuitive and ergonomic

Integral TwinControl:

Exclusive patented system doubling the essential oven functions

Full Cleaning System: (option)

Cleaning system with automatic chemical supply



TECHNICAL SPECIFICS

- * VisioPAD® toughened glass control panel: comprising a large colour LCD touch screen and coding knob.
- * **CoreControl:** Automatic adjustment of the oven power to suit the load being cooked, for results that are always to the precise degree required.
- * Continuously available thanks to immediate adjustment to the required temperature.
- * **Aircontrol:** Auto reverse ventilation, adjustable from 1 to 100%.
- * **Airdry+ :** Rapid product drying by opening the motorised vent, for a crisper exterior, ventilation provided by 3 fans..
- * Power down : Automatically switches to energy saving mode after a period of inactivity (adjustable).
- * The oven can be preheated out of hours.
- * Cooking cavity, a capacity of **20 levels** for GN 1/1 (325 x 530mm) spaced **65mm** apart.
- * Semi-automatic cleaning programme ensures regular cleaning at optimum temperature out of hours.
- * **6 cooking modes:**
 - Convection from 0 to 250°C
 - Saturated steam: steam to 98°C
 - Combined from 30 to 250°C (with humidity adjustable from 0 to 99%)
 - Low temperature: steam from 30 to 97°C
 - High temperature steam: steam from 99 to 105 °C
 - Regeneration.
- * **Automatic cooking menu:**
 - Immediate access to cooking programmes
 - Preloaded recipes as standard with the option to adjust the degree of cooking and the colouration
 - It is possible to create entirely personalised recipes.
- * **Functions**
 - **Automatic oven cavity cooling**, door closed: improved reactivity
 - **Humidifier** : provides instant steam (shot of vapour): ideal for bread
 - **Hold function** : temperature holding phase after cooking (semi static oven). Avoids the surface of the product drying out
 - **Automatic rinse** possible between cooking operations, replaces the spray hose.
- * **Service menu**
 - Exchanges and backup of recipes via the USB port (Accessory)
 - Parameters can be modified to give maximum personalisation.
- * **Equipment**
 - Cool touch athermic double glazed clipped door with left hand rotation of the handle to open, hinged to the left and manual closure mechanism. Opens to 180° with hinged internal glass to make cleaning easier
 - Cavity illumination by a strip of LEDs in the door
 - Condensation recovery channel under the door and below the oven drains continuously
 - Seal clipped onto the facia ("protected from rubbing against the edges of ovenware as it is loaded")
 - Features electrical protection, a door safety and thermal overload protection.
- * **Standard supply**
 - 20 level stainless steel trolley with 4 castors, 2 braked (see specific technical data sheet)
 - Core probe socket allowing the use of a removable core probe (Accessory)
 - Electrical connection points for an energy economiser.

ACCESSORIES / OPTIONS

- * Additional oven trolley (see specific technical data sheet).
- * Plate holder trolley and insulated cover for banqueting (see specific technical data sheet).
- * USB port kit.
- * Removable core probe:
 - Delicate product probe 2.5mm diameter 100mm long
 - Rotisserie core probe 4.5mm diameter 100mm long
- * Preheating plate (an oven trolley does not need to be placed in the oven whilst pre-heating).
- * Retracting spray hose kit.
- * Independant spray hose kit.
- * HACCP record output kit: HACCP outlet comprises 2 x 10m copper cables exiting the rear.
- * Grills (3 or 5).
- * Three phase 230V + Earth option.
- * 60Hz option.
- * «FullCleaning System» Automatic cleaning option: Automatic cleaning with integral cleaning chemical pump. 4 possible levels of cleaning.

NORMS: Conforms to

EN 60-335-2-42: European norm relating to the safety of electrical appliances.

(French norm: classification index C 73-842).

IP 25 and IK 9: Protection indices.

XP U 60-010: Hygiene.

BEJE201-1-11

- ELECTRICAL connection**
Electric inlet at 375mm from the floor.
Protection required:
- 400V: 50A MCB (Miniature Circuit Breaker) with B curve and 30mA RCD (Residual Current Device)
- 230V: 80A MCB (Miniature Circuit Breaker) with B curve and 30mA RCD (Residual Current Device)

- Potable COLD WATER**
Water inlet at 220mm from the floor.
A local stop cock is required.


- SOFTENED WATER**
Water inlet at 220mm from the floor.
A local stop cock is required.

- DRAIN**
Drain outlet at 180mm from the floor.
The water discharged could be condensate and at very high temperature, use material that is suitable for high temperatures.
There must be a trap between the unit and the mains drainage to prevent odours.

- Vent with choke**

- Exit for surplus steam**

- Horizontal floor with a 1 cm/m maxi slope**



MODEL	BEJE201-1-11
--------------	--------------

DIMENSIONS (mm)	
External	Height 1947; Width 990; Depth 862
Cavity	Height 1446; Width 630; Depth 535

CAPACITIES	
Number of covers per day	470
Usable oven capacity (dm ³)	225
GN 1/1 ovenware (325 x 530)	20
Max. depth of containers (mm)	55
Space between levels (mm)	65
Maximum capacity (kg)	80

PACKAGING (mm)	
Height	2000
Width x Depth	1200 x 1000

WEIGHT (KG) (gross / net)	289 / 225 + 30 (oven + trolley)
----------------------------------	---------------------------------

CLEARANCES	Left: 4cm ; Right: 50cm
-------------------	-------------------------

TEMPERATURE RANGE	0 to 250°C
--------------------------	------------

CORE TEMPERATURE RANGE	0-99°C
-------------------------------	--------

TIMER	99 hours
--------------	----------

ELECTRICITY (Three phase 230V+E or 400V+N+E)		
Voltage	I. Max (A)	Power (kW)
230V 3a.c.	70.4	27.7
400V 3Na.c.	42.4	27.7

POTABLE COLD Water / SOFTENED Water	
Pressure (Min / Max)	150/600 kPa (1.5 bar / 6 bar)
Cold water max temperature	23°C
Softened water max temperature	23°C
Nature	168 µm filter integral with the oven
Hardness (Softened water)	TH 4 to 7 °e (60 to 100 ppm)
Water quality	Chloride Cl ⁻ : ≤ 150 mg/l / Free Chlorine Cl ₂ : ≤ 0.2 mg/l / 6.5 ≤ PH ≤ 9
Conductivity	≥ 50 µS / cm
Connection	20/27 threaded (G 3/4)
Instant maximum consumption	10 L/min

DRAIN	
Condensate temperature	Approx. 98°C
Connection	Vertical exit 40/49 threaded stainless (G 1"1/2)

CONSTRUCTION	
Cavity and Cladding	18-10 Stainless

EQUIPMENT TYPE	Against a wall - Not stackable
-----------------------	--------------------------------