



## BGBF10 - Lincat Blu Blast Chiller - 10 Trays

Perfect for large batch cooking, where large quantities of food need to be brought down to storage temperature quickly

- ✔ Quickly and efficiently pull down the temperature of cooked foods
- ✔ Perfect for large batch cooking, where large quantities of food need to be brought down to storage temperature quickly
- ✔ Reduce a product's core temperature from 90°C to 3°C within 90 minutes
- ✔ With shock freezing cycle - allows the nutritional properties, appearance and flavour of a product to be maintained after thawing
- ✔ Core probe needle as standard
- ✔ Indirect air flow guarantees a perfect temperature throughout the unit
- ✔ GN1/1 and Euronorm 600 x 400 compatible - load 10 trays onto the side racks
- ✔ Side racks removable without tools for easy cleaning
- ✔ Easy-to-use digital controls - simple buttons for soft blast chilling, hard blast chilling, and shock freezing cycles, as well as manual time/temperature controls
- ✔ Auto-defrost function
- ✔ Radiused interior corners enable easy cleaning
- ✔ Reversible self-closing door with 105 degree stop
- ✔ High efficiency 60mm cyclopentane insulation - zero ODP (Ozone Depletion Potential) and only a low GWP (Global Warming Potential), providing excellent thermal efficiency
- ✔ Wide magnetic gasket gives effective seal, easily removable for cleaning
- ✔ Hygienic and robust design - Grade 304 stainless steel interior and exterior, radiused interior corners to promote easy cleaning

### Specifications

Summary		Power and Performance	
<b>Brand</b>	Lincat	<b>Total Power kW</b>	2.8
<b>Range</b>	Blu	<b>Temperature Range °C</b>	+20 to -40
<b>Power Type</b>	Electric	<b>Temperature Control</b>	Electronic
<b>Unit Type</b>	Free-standing	<b>Cooling Capacity Watts</b>	4,906W / 1,072W
<b>Available in UK Only</b>	No	<b>Climate Class</b>	5
<b>UK Warranty</b>	2 Years Parts and Labour (3 Years on Compressor)		
<b>Export Warranty</b>	Contact your local dealer		
<b>GTIN</b>	5056105123378		

Key Specifications		Capacity	
<b>Lockable Door</b>	No	<b>Gastronorm Capacity</b>	GN1/1, Euronorm
<b>Number of Doors</b>	1	<b>Chilling Capacity kg</b>	30
<b>Reversible Door</b>	Yes	<b>Chilling Time mins</b>	90
<b>Number of Shelf Positions</b>	10	<b>Freezing Capacity kg</b>	20
<b>Refrigerant Type</b>	R452a	<b>Freezing Time mins</b>	270
<b>Construction/Finish</b>	304 Grade S/S Ext/Int		
<b>Base Mounting</b>	Castors		
<b>Insulation Material/Thickness</b>	Cyclopentane / 60 mm		
<b>Maximum Ambient Temperature °C</b>	38		
<b>Auto Defrost</b>	Yes		
<b>HACCP Compliant</b>	Yes		
<b>Number of Shelves</b>	0		
<b>Shelf Supports</b>	Anti-tilt		
<b>Integral Handle</b>	Yes		
<b>Self Close Door</b>	Yes		

Weights and Dimensions		Supply Connections	
Unit Height (External) mm	1630	Requires Installation	Yes
Unit Width (External) mm	800	Requires Electrical Supply	Yes
Unit Depth (External) mm	830	UK 3 Pin Plug	No
Net Weight Kg	195	Requires Hardwiring	Yes
		Electrical Supply Rating Watts	2,800
		Single Phase Amps	11
		Single Phase Voltage	230

Shipping	
Packed Weight Kg	200
Packed Height cm	176
Packed Width cm	85
Packed Depth cm	88



**Lincat Limited**

Whisby Road,  
Lincoln, LN6 3QZ,  
United Kingdom

**Company No:** 2175448

A member company of



**Customer Care**

**Tel:** +44 1522 875500  
**Email:** care@lincat.co.uk

**Export Customers**

**Tel:** +44 1522 875536  
**Email:** export@lincat.co.uk

**Opening Hours**

**Monday – Friday:**  
8.30am – 5pm