



## BGBF5P - Lincat Blu Blast Chiller - 5 Trays

Perfect for large batch cooking, where large quantities of food need to be brought down to storage temperature quickly

- ✔ Quickly and efficiently pull down the temperature of cooked foods
- ✔ Perfect for large batch cooking, where large quantities of food need to be brought down to storage temperature quickly
- ✔ Reduce a product's core temperature from 90°C to 3°C within 90 minutes
- ✔ With shock freezing cycle - allows the nutritional properties, appearance and flavour of a product to be maintained after thawing
- ✔ Core probe needle as standard
- ✔ Indirect air flow guarantees a perfect temperature throughout the unit
- ✔ GN1/1 and Euronorm 600 x 400 compatible - load 5 trays onto the side racks
- ✔ Side racks removable without tools for easy cleaning
- ✔ Easy-to-use digital controls - simple buttons for soft blast chilling, hard blast chilling, and shock freezing cycles, as well as manual time/temperature controls
- ✔ Auto-defrost function
- ✔ Radiused interior corners enable easy cleaning
- ✔ Reversible self-closing door with 105 degree stop
- ✔ High efficiency 60mm cyclopentane insulation - zero ODP (Ozone Depletion Potential) and only a low GWP (Global Warming Potential), providing excellent thermal efficiency
- ✔ Wide magnetic gasket gives effective seal, easily removable for cleaning
- ✔ Hygienic and robust design - Grade 304 stainless steel interior and exterior, radiused interior corners to promote easy cleaning

### Specifications

#### Summary

<b>Brand</b>	Lincat
<b>Range</b>	Blu
<b>Power Type</b>	Electric
<b>Unit Type</b>	Free-standing
<b>Available in UK Only</b>	No
<b>UK Warranty</b>	2 Years Parts and Labour (3 Years on Compressor)
<b>Export Warranty</b>	Contact your local dealer
<b>GTIN</b>	5056105123361

#### Power and Performance

<b>Total Power kW</b>	0.8
<b>Temperature Range °C</b>	+20 to -40
<b>Temperature Control</b>	Electronic
<b>Cooling Capacity Watts</b>	2,095W / 615W
<b>Climate Class</b>	5

#### Key Specifications

<b>Lockable Door</b>	No
<b>Number of Doors</b>	1
<b>Reversible Door</b>	Yes
<b>Number of Shelf Positions</b>	5
<b>Refrigerant Type</b>	R452a
<b>Construction/Finish</b>	304 Grade S/S Ext/Int
<b>Base Mounting</b>	Castors
<b>Insulation Material/Thickness</b>	Cyclopentane / 60 mm
<b>Maximum Ambient Temperature °C</b>	38
<b>Auto Defrost</b>	Yes
<b>HACCP Compliant</b>	Yes
<b>Number of Shelves</b>	0
<b>Shelf Supports</b>	Anti-tilt
<b>Integral Handle</b>	Yes
<b>Self Close Door</b>	Yes

#### Capacity

<b>Gastronorm Capacity</b>	GN1/1, Euronorm
<b>Chilling Capacity kg</b>	14
<b>Chilling Time mins</b>	90
<b>Freezing Capacity kg</b>	8
<b>Freezing Time mins</b>	270

Weights and Dimensions		Supply Connections	
------------------------	--	--------------------	--

Unit Height (External) mm	850	Requires Installation	Yes
Unit Width (External) mm	800	Requires Electrical Supply	Yes
Unit Depth (External) mm	800	UK 3 Pin Plug	No
Net Weight Kg	105	Requires Hardwiring	Yes
		Electrical Supply Rating Watts	800
		Single Phase Amps	5
		Single Phase Voltage	230

**Shipping**

Packed Weight Kg	125
Packed Height cm	102
Packed Width cm	85
Packed Depth cm	84



**Lincat Limited**

Whisby Road,  
Lincoln, LN6 3QZ,  
United Kingdom

**Company No:** 2175448

A member company of



**Customer Care**

**Tel:** +44 1522 875500  
**Email:** care@lincat.co.uk

**Export Customers**

**Tel:** +44 1522 875536  
**Email:** export@lincat.co.uk

**Opening Hours**

**Monday – Friday:**  
8.30am – 5pm