BLUE SEAL EVOLUTION SERIES®

Technical data sheet for

TWIN PAN ELECTRIC FRYER 450mm

F44

- 17kW high performance twin pan fryer
- Easy clean stainless steel open pan with 10 year limited warranty
- 12L per pan oil capacity
- 25mm (1") drain valves
- Rear rollers
- Stainless steel exterior
- Easy service
- Fully modular



Overall Construction

- Stainless steel pan with 10 year limited warranty
- Bull nose welded 1.5mm stainless steel
- Splashback 1.2mm stainless steel
- Side panels 1.2mm stainless steel
- Double skin door with 0.9mm stainless exterior
- Enamelled control panel
- Hinge out counterbalanced heating elements
- 25mm (1") drain valves
- 63mm dia. heavy-duty 1.2mm stainless steel adjustable legs at front and two rollers at rear
- 2 baskets and stainless steel lid supplied standard

Controls

- Mechanical thermostats
- Thermostat range 60-200°C
- Large easy use controls with easy view scale
- Fail-safe over-temperature safety cut-outs
- Element tilt switch for heating cut-out on element lift
- Indicator lights for power and heating (per pan)

Cleaning and Servicing

- Open stainless steel pans for easy clean
- Easy clean basket support bar
- \bullet 25mm (1") drain valves for effective draining
- Easy clean stainless steel exterior
- Access to all parts from front of unit

Technical data sheet for

TWIN PAN ELECTRIC FRYER 450mm

Specifications

Production rate

31kg/hr

Pan Size (per pan)

Oil capacity 12L (24lbs shortening) per pan Width 175mm Length 380mm Oil frying depth 95mm

Baskets

2 chrome plated wire baskets 140mm W x 335mm D x 145mm H

Elements (per pan)

3 x 2.83kW stainless steel heating elements

Electrical requirements

17kW, 400-415Vac, 50/60hz, 3P+N+E

L1 23.6A L2 23.6A L3 23.6A

Dimensions

Width 450mm Depth 812mm Height 915mm

Incl. splashback 1085mm

Nett weight

73kg


Packing data


0.54m3, 114kg Width 870mm Depth 495mm Height 1255mm

Options

Adjustable feet at rear Filtamax Filtration System Extra baskets Side splash guards Joining caps Castors

E44







OBLUE SERL

www.blue-seal.co.uk www.bluesealevolution.com

United Kingdom Blue Seal Limited

Unit 67

Gravelly Business Park

Gravelly

Birmingham B24 8TQ

England

Telephone 0121-327 5575

Facsimile 0121-327 9711

Email sales@blue-seal.co.uk

www.blue-seal.co.uk

Australia Moffat Pty Limited

740 Springvale Rd

Mulgrave

Victoria 3170

Australia

Telephone 03-9518 3888

Facsimile 03-9518 3833

Email vsales@moffat.com.au

www.moffat.com.au

New Zealand Moffat Limited

16 Osborne St

P0 Box 10-001

Christchurch 8011

New Zealand

Telephone 03-389 1007

Facsimile 03-389 1276

Email sales@moffat.co.nz

www.moffat.co.nz



ISO9001 Quality Management Standard

Designed and manufactured by



IS09001

All Blue Seal products are designed and manufactured by Moffat using the internationally recognised IS09001 quality management system, covering design, manufacture and final inspection, ensuring consistent high quality at all times.

CE

In tine with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice.

