



## BPETM3 - Lincat Blu Counter Fridge - Triple Door

Ideal multifunctional solution for kitchens with limited prep space.

- ✓ Ideal multifunctional solution for kitchens with limited prep space
- ✓ Accurate electronic temperature control with easy-to-use digital controls to ensure safe storage of foods
- ✓ Practical solid worktop - use as a prep area, with quick access to fresh ingredients at the point of preparation
- ✓ GN1/1 compatible
- ✓ Load gastronorms directly onto the rails for ease of loading, or use the shelf supplied for flexible chilled storage
- ✓ Supplied with 1 shelf per cabinet
- ✓ 6 shelf positions per cabinet allows flexibility
- ✓ Fan assisted for optimal air distribution, ensures efficient and safe operation even when the shelves are fully loaded
- ✓ Auto-defrost function
- ✓ Hygienic and robust design - Grade 304 stainless steel interior and exterior, radiused interior corners and removable shelf supports to promote easy cleaning
- ✓ Full width easy grab handles
- ✓ 50mm cyclopentane insulation and R290 gas - zero ODP (Ozone Depletion Potential) and only a low GWP (Global Warming Potential), providing excellent thermal efficiency
- ✓ Heavy duty 2 swivel castors with 2 braked for easy manoeuvring and safety

### Specifications

#### Summary

<b>Brand</b>	Lincat
<b>Range</b>	Blu
<b>Power Type</b>	Electric
<b>Unit Type</b>	Free-standing
<b>Available in UK Only</b>	No
<b>UK Warranty</b>	2 Years Parts and Labour (3 Years on Compressor)
<b>Export Warranty</b>	Contact your local dealer
<b>GTIN</b>	5056105123354

#### Power and Performance

<b>Total Power kW</b>	0.27
<b>Temperature Range °C</b>	-2 to +8
<b>Temperature Control</b>	Electronic
<b>Cooling Capacity Watts</b>	425
<b>Energy Grade</b>	C
<b>Annual Energy Consumption kWh/Annum</b>	1,217
<b>Climate Class</b>	5
<b>Energy Consumption kW/24hrs</b>	3.334

#### Key Specifications

<b>Lockable Door</b>	No
<b>Number of Doors</b>	3
<b>Shelf Material</b>	Plastic coated steel
<b>Reversible Door</b>	No
<b>Number of Shelf Positions</b>	18
<b>Refrigerant Type</b>	R290
<b>Construction/Finish</b>	S/S 304 (int / ext)
<b>Base Mounting</b>	Castors
<b>Insulation Material/Thickness</b>	Cyclopentane / 50 mm
<b>Maximum Ambient Temperature °C</b>	+40
<b>Auto Defrost</b>	Yes
<b>HACCP Compliant</b>	No
<b>Number of Shelves</b>	3
<b>Integral Handle</b>	Yes
<b>Self Close Door</b>	No

#### Capacity

<b>Gastronorm Capacity</b>	GN1/1
<b>Capacity Litres</b>	428

Weights and Dimensions		Supply Connections	
------------------------	--	--------------------	--

Unit Height (External) mm	850	Requires Installation	No
Unit Width (External) mm	1780	Requires Electrical Supply	Yes
Unit Depth (External) mm	700	UK 3 Pin Plug	Yes
Net Weight Kg	155	Requires Hardwiring	No
		Electrical Supply Rating Watts	270
		Single Phase Amps	1.7
		Single Phase Voltage	230

**Shipping**

Packed Weight Kg	175
Packed Height cm	11
Packed Width cm	183
Packed Depth cm	78



**Lincat Limited**

Whisby Road,  
Lincoln, LN6 3QZ,  
United Kingdom

**Company No:** 2175448

A member company of



**Customer Care**

**Tel:** +44 1522 875500  
**Email:** care@lincat.co.uk

**Export Customers**

**Tel:** +44 1522 875536  
**Email:** export@lincat.co.uk

**Opening Hours**

**Monday – Friday:**  
8.30am – 5pm