

CO223M - Lincat Convector Manual+ Electric Counter-top Convection Oven - W 810 mm - D 850 mm - 3.0 kW

- 2 x GN1/1 capacity
- Easy-to-use knob-driven control, and electronic fan control
- Mechanical temperature control from 60° to 260° C
- Even heat distribution thanks to electronically controlled two-speed, bi-directional fan

Able to roast, braise, bake and reheat, a CO223M Convector convection oven is a powerful addition to any commercial kitchen.

- Two fan speeds standard for general use and slow for delicate items
- 120 minute count down timer with electronicallycontrolled buzzer
- Oven lamps flash when cook cycle has finished see when your food is done even in the busiest kitchen

## **Specifications**

#### Summary

Brand Range Series Power Type Unit Type Available in UK Only UK Warranty Export Warranty GTIN Lincat Convector Manual+ Electric Counter-top No 2 Years Parts and Labour Warranty Contact your local dealer 5056105118268

## **Power and Performance**

Total Power kW Temperature Range °C IP Rating Controls Position Temperature Control Timer Range mins Oven Rating kW 3.0
60-260
IP23
Right hand side
Mechanical
1-120
2.8

## lincat

## CONVECTOR

Key Specifications		Capacity	
tackable	Yes (with optional kit)	Gastronorm Capacity	2 x GN1/1
eet Height/Type	55mm/adjustable	Euronorm Capacity	2 x 600 mm x 400 mm
Continuous Plug-In Door Seal	Yes	Shelf Spacing mm	110
Removable Inner Door Glass	Yes	Sheet Pan Capacity	2 x 660 mm x 460 mm
landle Type	Grab	Capacity Litres	96.0
/ented Door	Yes		
Reversible Door	No		
Door Type	Drop down		
Phased Cooking	No		
Shelf Timer(s) (Number)	No		
Grill Element/Mode	No		
Core Temp Probe	No		
Steam Injection	No		
Fan(s) Speed	2		
Fan(s) Type	Bi-Directional		
Number of Fan(s)	1		
Euronorm Compatible	Yes		
Sheet Pan Compatible	Yes		
Removeable Shelf Guides	Yes		
Manual Mode	Yes		
Programmable	No		
Timer Type	Mechanical		
Number of Shelves included	2		
Number of Shelf Positions	2		
Type of Lighting	Halogen Bulb		
Construction/Finish	430 S/S cavity		
GN Compatible	Yes		
Weights and Dimensions		Supply Connections	
Unit Height (External) mm	645	Requires Installation	No
Jnit Width (External) mm	810	Requires Electrical Supply	Yes
Jnit Depth (External) mm	850	UK 3 Pin Plug	Yes
Height (Internal) mm	308	Requires Hardwiring	No
Width (Internal) mm	690	Electrical Supply Rating Watts	3,000
Depth (Internal) mm	470	Single Phase Amps	13.0
Shelf Dimensions Width mm	660	Single Phase Voltage	230
Shelf Dimensions Depth mm	425	USB Port	No
Not Welshift Ka	<b>TO 0</b>		

## Shipping


Net Weight Kg


Packed Weight Kg	86.79
Packed Height cm	81.5
Packed Width cm	88
Packed Depth cm	100


78.9

Available Accessories		
CO200/FS	Lincat Convector Floor Stand for C0223M/C0223T/C0235M/C0235T Convection Ovens - with 4 Runners - W 810 mm	
CO200/LFSK	Lincat Convector Low Floor Stand and Stacking Kit for CO223M/CO223T/CO235M/CO235T Convection Ovens - with 1 Runner - W 810 mm	

## **Technical Picture**







# Lincat fift

## Lincat Limited

Whisby Road, Lincoln, LN6 3QZ,

United Kingdom

Company No: 2175448

A member company of



Customer Care

Tel: +44 1522 875500 Email: care@lincat.co.uk

### **Export Customers**

Tel: +44 1522 875536

Email: export@lincat.co.uk

### **Opening Hours**

Monday – Friday: 8.30am – 5pm