

CO223T - Lincat
Convector Touch Electric
Counter-top Convection
Oven - W 810 mm - D 850
mm - 3.0 kW

Able to roast, braise, bake and reheat, a CO223T Convector convection oven is a powerful addition to any commercial kitchen.

- 2 x GN1/1 capacity
- Touchscreen control with easy-to-use icon-driven menu selections
- Easy-view traffic light status see the status of the oven at a glance, even in the noisiest kitchens
- Space for 24 programs with up to four stages, which can be adjusted individually
- Up to four-stage phased cooking for perfect results - set temperature, time, fan speed and humidity injection for each stage
- Even heat distribution thanks to electronically controlled two-speed, bi-directional fan
- Five levels of humidity injection
- Nine-hour on-screen timer, with electronic buzzer, and flashing oven lamps to indicate that cycle has finished

Specifications Power and Performance Summary Total Power kW **Brand** 3.0 Range Convector Temperature Range °C 30-260 Series **IP Rating** IP23 Touch **Power Type** Electric **Controls Position** Right hand side **Unit Type Temperature Control** Electronic Counter-top Available in UK Only Timer Range mins 1-540 **UK Warranty** 2 Years Parts and Labour Warranty Oven Rating kW 2.8 **Export Warranty** Contact your local dealer GTIN 5056105118275

Key Specifications		Capacity	
Stackable	Yes (with optional kit)	Gastronorm Capacity	2 × GN1/1
Feet Height/Type	55mm/adjustable	Euronorm Capacity	2 x 600 mm x 400 mm
Continuous Plug-In Door Seal	Yes	Shelf Spacing mm	110
Removable Inner Door Glass	Yes	Sheet Pan Capacity	2 x 660 mm x 460 mm
Handle Type	Grab	Capacity Litres	96.0
Vented Door	Yes		
Reversible Door	No		
Door Type	Drop down		
Number of Cooking Phases	4		
Phased Cooking	Yes		
Shelf Timer(s) (Number)	Yes(4)		
Grill Element/Mode	No		
Core Temp Probe	No		
Steam Injection	Yes		
Fan(s) Speed	2		
Fan(s) Type	Bi-Directional		
Number of Fan(s)	1		
Euronorm Compatible	Yes		
Sheet Pan Compatible	Yes		
Removeable Shelf Guides	Yes		
Manual Mode	Yes		
Programmable	Yes		
Number of Programs	24(4 stages)		
Timer Type	Touchscreen		
Display Type	Touchscreen		
Number of Shelves included	2		
Number of Shelf Positions	2		
Type of Lighting	Halogen Bulb		
Construction/Finish	304 S/S cavity		
GN Compatible	Yes		
Weights and Dimensions		Supply Connections	
Unit Height (External) mm	645	Requires Installation	No
Unit Width (External) mm	810	Requires Electrical Supply	Yes
Unit Depth (External) mm	850	UK 3 Pin Plug	Yes
Height (Internal) mm	308	Requires Hardwiring	No
Width (Internal) mm	690	Electrical Supply Rating Watts	3,000
Depth (Internal) mm	470	Single Phase Amps	13.0
Shelf Dimensions Width mm	660	Single Phase Voltage	230
Shelf Dimensions Depth mm	425	Water Connection Pressure Bar	2.0-6.0
Net Weight Kg	80	Drain Connection	No
		Water Connection	3/4" BSPT
		USB Port	Yes
Shipping			
Packed Weight Kg	88		
Packed Height cm	81.5		
Packed Width cm	88		
Packed Depth cm	100		
•			

Available Accessories


ACIK04 Water Treatment Filter Kit


CO200/FS $Lincat\ Convector\ Floor\ Stand\ for\ CO223M/CO223T/CO235M/CO235T\ Convection\ Ovens-with\ 4\ Runners-W\ 810\ mm$


 $Lincat \, Convector \, Low \, Floor \, Stand \, and \, Stacking \, Kit \, for \, CO223M/CO223T/CO235M/CO235T \, Convection \, Ovens \, - \, with \, 1 \, Runner \, -$ CO200/LFSK

810 mm

Technical Picture









Lincat Limited

Whisby Road,

Lincoln, LN6 3QZ,

United Kingdom

Company No: 2175448

A member company of

Customer Care

Tel: +44 1522 875500

Email: care@lincat.co.uk

Export Customers

Tel: +44 1522 875536

Email: export@lincat.co.uk

Opening Hours

Monday - Friday:

8.30am - 5pm