

CO235M - Lincat
Convector Manual+
Electric Counter-top
Convection Oven - W 810
mm - D 850 mm - 4.8 kW

Able to roast, braise, bake and reheat, a CO235M Convector convection oven is a powerful addition to any commercial kitchen.

- 3 x GN1/1 capacity
- Easy-to-use knob-driven control, and electronic fan control
- Mechanical temperature control from 60° to 260° C
- Even heat distribution thanks to electronically controlled two-speed, bi-directional fan
- Two fan speeds standard for general use and slow for delicate items
- 120 minute count down timer with electronicallycontrolled buzzer
- Oven lamps flash when cook cycle has finished see when your food is done even in the busiest kitchen

Specifications Summary Power and Performance Brand Lincat Total Power kW 4.8 Range Convector Temperature Range °C 60-260 Series IP Rating IP23 Manual+ **Power Type Controls Position** Electric Right hand side Temperature Control **Unit Type** Counter-top Mechanical Available in UK Only Timer Range mins 1-120 **UK Warranty** Oven Rating kW 2 Years Parts and Labour Warranty 4.6 **Export Warranty** Contact your local dealer **GTIN** 5056105118282

Key Specifications Capacity Stackable **Gastronorm Capacity** 3 x GN1/1 Yes (with optional kit) **Euronorm Capacity** Feet Height/Type 3 x 600 mm x 400 mm 55mm/adjustable Continuous Plug-In Door Seal Shelf Spacing mm **Removable Inner Door Glass** Yes **Sheet Pan Capacity** 3 x 660 mm x 460 mm **Handle Type Capacity Litres** 96.0 Grab Vented Door Yes Reversible Door Νn Door Type Drop down **Phased Cooking** No Shelf Timer(s) (Number) No Grill Element/Mode No **Core Temp Probe** No Steam Injection No Fan(s) Speed 2 Fan(s) Type Bi-Directional Number of Fan(s) **Euronorm Compatible** Yes **Sheet Pan Compatible** Removeable Shelf Guides Yes **Manual Mode** Yes Programmable No Timer Type Mechanical Number of Shelves included 3 **Number of Shelf Positions** 3 Type of Lighting Halogen Bulb Construction/Finish 430 S/S cavity **GN** Compatible Yes

Supply Connections		Weights and Dimensions	
	Requires Installation	645	Unit Height (External) mm
	Requires Electrical Supply	810	Unit Width (External) mm
	UK 3 Pin Plug	850	Unit Depth (External) mm
	Requires Hardwiring	308	Height (Internal) mm
	Electrical Supply Rating Watts	690	Width (Internal) mm
	Single Phase Amps	470	Depth (Internal) mm
	Single Phase Voltage	660	Shelf Dimensions Width mm
=6.9; L3=6.9	Three Phase Amps	425	Shelf Dimensions Depth mm
	Three Phase Voltage	80.6	Net Weight Kg
	USB Port		
:6	Three Phase Voltage		·

Shipping

 Packed Weight Kg
 88.66

 Packed Height cm
 81.5

 Packed Width cm
 88

 Packed Depth cm
 100


Available Accessories


CO200/FS Lincat Convector Floor Stand for CO223M/CO235M/CO235T Convection Ovens - with 4 Runners - W 810 mm


CO200/LFSK Lincat Convector Low Floor Stand and Stacking Kit for C0223M/C0223T/C0235M/C0235T Convection Ovens - with 1 Runner - W

810 mm

Technical Picture









Lincat Limited

Whisby Road,

Lincoln, LN6 3QZ,

United Kingdom

Company No: 2175448

A member company of

Customer Care

Tel: +44 1522 875500

Email: care@lincat.co.uk

Export Customers

Tel: +44 1522 875536

Email: export@lincat.co.uk

Opening Hours

Monday - Friday:

8.30am - 5pm