RACK CONVEYOR DISHWASHERS

The Ecomax Plus rack conveyors are truly outstanding in their field, delivering ease of use and low running costs. Designed for higher volume operations, the machines ensure a gleaming finish without fail.

ECOMAX PLUS C803A

- Wash up to 110 racks per hour (1,980 plates)
- Compact design – just 1350mm in length
- Stainless steel wash arms with anti-block jets
- Optional dryer and heat recovery available

Turn over for full machine specs.

ECOMAX PLUS C803EA

- Effective pre-wash feature for optimal wash results
- Large wash capacity – wash up to 140 racks per hour (2,520 plates)
- Stainless steel wash arms with anti-block jets
- Optional dryer and heat recovery available

SPECIFICATIONS	ECOMAX PLUS	ECOMAX PLUS
GENERAL	**C803A**	**C803EA** (PRE-WASH)
DIMENSIONS	1350mm(w)	1850mm(w)
	785mm(d)	785mm(d)
	1961mm(h)	1961mm(h)
Number of racks/hr	110	140
Rack size	500 x 500mm	500 x 500mm
Racks supplied	1 x plate rack	1 x plate rack
	1 x cup rack	1 x cup rack
	1 x cutlery basket	1 x cutlery basket
Max plates per rack	18	18
Rinse booster pump	YES	YES
CONTROLS	ELECTRONIC	ELECTRONIC
Class A air gap	YES	YES
Rinse water consumption	230ltrs/hr	240ltrs/hr
Pre-wash tank capacity	-	10ltrs
Wash tank capacity	105ltrs	105ltrs
Wash tank heating	12kW	12kW
Pre-wash pump rating	-	0.27kW
Pre-wash pump flow rate	-	20ltrs/min
Wash pump rating	1.5kW	1.5kW
Wash pump flow rate	350 ltrs/min	350 ltrs/min
Noise level	64dB	64dB
Dryer	Optional	Optional
Drying tunnel length	650mm	650mm
Drying tunnel loading	3.5kW	3.5kW
Heat recovery	Optional	Optional
Circulation	800m3/hr	800m3/hr
Reduction in kW loading	6kW	6kW
WATER		
Water flow pressure	1.5 – 6 BAR	1.5 – 6 BAR
ELECTRIC		
Total connected load (water fed @ 40°C)	26.8kW	26.9kW
Total connected load (water fed @ 10°C)	35.8kW	35.9kW
DRAIN		
Drain size(diameter in inches)	50mm	50mm
Max height above floor level	185mm	185mm

ECOMAX PLUS C803A

ECOMAX PLUS C803EA

Tabling not included.

Technical details may be subject to change at any time without prior notice.