





ÖZT RYAK LER
Cumhuriyet Mah. Hadımköy Yolu Cad. No:8
Büyükcçekmece- stanbul-TURKEY
e-mail: export@oztiryakiler.com.tr
web: www.oztiryakiler.com.tr

Code:
7867.N1.10908.02

Tilting Bratt Pan 900 Serie Gas 100 lt. 100*90

model:
OTG 100



MAIN FEATURES

2 mm thick AISI 304 stainless steel laser cut top
Flush top setting with secure fixing screws
3 installation options; standalone(fixed on a base w/ or w/o door), cantilever or on concrete plinth
Installation gap behind the equipment for plumbing & electrical connections
Gas appliances supplied for use with natural or LPG gas, conversion jets supplied as standard.
Easy access from front panel to all major components for maintenance
Modular system for flexibility

CONSTRUCTION

All stainless steel construction to avoid any infiltration
Top, sides, back, front panels and control consoles in stainless steel with satin scotch-brite finish
Standalone and base units are equipped with heavy duty 150 mm adjustable stainless feet.

ADDITIONAL FEATURES

Corrosion resistance 8 mm stainless steel pan bottom
Optional 10 mm thick duomat cooking surface with the combination of 2 different stainless steel for better thermal stability
available on request
Rounded pan corners for increased hygiene
Electronic ignition system with indicator lamp
Automatic gas cut off during tilting
Safety thermostat against overheating
Thermostatic temperature control between 50-300°C
High quality thermal insulation for limited heat radiation and low energy consumption
Double skin lid with counter balanced mechanism for easy opening
Manuel wheel-operated tilt mechanism
Solenoid valve and chromed swivel tap on top to refill hot and cold water
Stainless steel burners with flame failure device for optimized combustion

OPTIONS

ACCESSORIES

STANDARTS & CERTIFICATES

EN 203-1
European Standard relating to the safety of gas appliances
EN 203-2-8
European Standard relating to the safety of gas appliances





ÖZT RYAK LER
Cumhuriyet Mah. Hadımköy Yolu Cad. No:8
Büyüçekmece- stanbul-TURKEY
e-mail: export@oztiryakiler.com.tr
web: www.oztiryakiler.com.tr

Code: 7867.N1.10908.02	Tilting Bratt Pan 900 Serie Gas 100 lt. 100*90	model: OTG 100

DIMENSIONS (Net)

* Depth (mm):	1000
* Width (mm):	900
* Height (mm):	850
* Weight (kg):	169

DIMENSIONS (Shipping)

* Depth (mm):	1090
* Width (mm):	1020
* Height (mm):	1150
* Volume (m3):	0,64

COMPOSITION OF TOP

COMPOSITION OF THE BOTTOM PART

GAS

* Power:	24	kW	81888	Btu/hr	20640	kcal	Gas Inlet:
* G20:	Natural Gas	Pressure:	20		2,5440	m3/h	
* G30 / 31:	LPG Gas	Pressure:	28-30/37	mbar			
* G30:	LPG Gas	Pressure:	30 / 50		1,8720	kg / h	

ELECTRICITY

* Power:	0,015	kW
* Supply Voltage:	230V - NF	50/60
* Protection Class:	IP21	

WATER-IN

* Cold Water Inlet:					
* Hot Water Inlet:		Pressure (min-max):	kPa	Temperature (min-max):	5-60 °C
* Hardness:	0-10				

DRAIN