# **GRAM COMPACT**

Compact refrigerators and freezers up to 600 litres



- go green with Gram





# GRAM COMPACT 210, 310, 410 and 610

- setting standards for the 21st Century
- setting standards for the 21st Century





### **GRAM COMPACT – lowest cost of ownership**

The GRAM COMPACT 210, 310, 410 and 610 range is setting new standards for Compact fridges and freezers around the world. This HFC free range offers ultra-low energy consumption - clearly making Gram cabinets top of their class. This will radically lower your cost of ownership and help you to reduce your Carbon Footprint.

### ... with versatile reliability

The Compact range are very reliable cabinets with 50 mm insulation, powerful cooling system and unique air distribution. This is your guarantee that they will meet the demanding requirements of todays professional kitchens.



### **Setting standards**

Ultra-low energy consumption guarantees you the lowest cost of ownership possible. A Compact K 410 refrigerator for instance consumes as little as 0.6 kWh/24, or 219 kWh/year. These trail blazing figures clearly demonstrate market leadership and state of the art product development (1).











### Wall mounted cabinet

Thanks to an external width of only 60 cm and depth of 64 cm Compact 210 cabinets take up little floor space. They can be used as undercounter, stacked or wall mounted.



### "Column" combination

Refrigerators and freezers have the same dimensions and are easily combined. The chosen combination can be ordered pre-mounted as an entire unit or be mounted on site.

Dimensions (W x D x H): 59,5 x 64 x 170 cm

### "Side-by-side" combination

Compact 210 cabinets can be placed side-by-side. Dimensions (W  $\times$  D  $\times$  H): 119  $\times$  64  $\times$  83 cm

● = Standard equipment | ○ = Optional equipment

GR/	AM COMPACT 210 Undercou	ınter refriq	erators, heio	ght 83 cm	
Product type		K 210 R	K 210 L	KG 210 R	KG 210 L
Temperature range		+2/+12	+2/+12	+2/+12	+2/+12
Refrigeration system		Ventilated	Ventilated	Ventilated	Ventilated
Defrost		Automatic	Automatic	Automatic	Automatic
Finish	External	Stainless	White	Stainless	White
	Internal	Grey ABS	White ABS	White ABS	White ABS
Fittings	Wire shelves (486 x 430 mm)	2 grey	2 white	2 white	2 white
	Wire shelves (486 x 300 mm)	1 grey	1 white	1 white	1 white
External equipment	Right-hinged, reversible door	•	•		
	Right-hinged glass door			•	•
	Door lock	•	•	•	•
	Integrated door handle	•	•	•	•
	Digital temperature display	•	•	•	•
	Adjustable skids at front, wheels at rear	•	•	•	•
	Left hinged door	0	0	0	0
	Legs (4 of) H=100/130 mm	0	0	0	0
	Castors (4 of) H=125 mm	0	0	0	0
	Marine legs (4 of) H=130/200 mm	0	0	0	0
	Stacking kit	0	0	0	0
	Wall suspension	0	0	0	0
Internal equipment	Internal lighting (LED)			•	•
	Additional wire shelves	0	0	0	0
	Stainless shelves	0	0	0	0
	Marine shelves	0	0	0	0
	Inclined shelves	0	0	0	0
	Wire basket	0	0	0	0
	60 Hz compressor	0	0	0	0

GR	GRAM COMPACT 210 Undercounter freezers, height 83 cm						
Product type		F 210 R	F 210 L				
Temperature range		-22/-5 -22/-5					
Refrigeration system		Ventilated Ventilated					
Defrost		Automatic Automatic					
Finish/equipment		like refrigerators (K 210) - see table above					
Ext./int. equipment		like refrigerators (K 210) - see table above					



## Ideal for kitchens with limited space

Lower height Compact 210 models are designed to fit under worktops in commercial workplaces. With their width of 60 cm, depth of 64 cm and height of just 83 cm, the cabinets are ideal for building in beneath worktops. This ensures that busy operators can have their raw materials stored close to hand.

Internal temperature stability is exceptional thanks to the Gram air distribution system. This means the Compact 210 cabinet maintains a correct and uniform temperature throughout. See illustration page 7.

Cabinets are available in stainless or white finish, with solid door. Refrigerators are also available with glass door. Stainless cabinets with solid door are designed with a durable grey inner

lining with matching grey wire shelves. White finish solid door have a white interior with matching wire shelves.

Both stainless steel and white refrigerators with glass door are with white inner lining with matching white wire shelves to have optimal light effect and display of the stored products inside the cabinet.

The list of equipment is long and includes, among other things, a ventilated air distribution system, automatic defrost with re-evaporation of defrost water, digital temperature display, door lock, wire baskets, marine equipment, 60 Hz compressor, suspension kit for wall hanging and stacking kit for column combinations.





### Wall mounted cabinet

The Compact 310 can also be wall mounted for easy floor cleaning.



### Combine with microwave oven

The "table top" of the cabinet is an ideal location for a piece of equipment such as a microwave oven, offering just the right ergonomic working height.



### "Side-by-side" combination

Compact 310 cabinets can be placed side-by-side. Dimensions (W  $\times$  D  $\times$  H): 119  $\times$  64  $\times$  130 cm.

	GRAM COMPACT 310 Re	frigerators,	height 130	cm	
Product type		K 310 R	K 310 L	KG 310 R	KG 310 L
Temperature range		+2/+12	+2/+12	+2/+12	+2/+12
Refrigeration system		Ventilated	Ventilated	Ventilated	Ventilated
Defrost		Automatic	Automatic	Automatic	Automatic
Finish	External	Stainless	White	Stainless	White
	Internal	Grey ABS	White ABS	White ABS	White ABS
Fittings	Wire shelves (486 x 430 mm)	3 grey	3 white	3 white	3 white
	Wire shelves (486 x 300 mm)	1 grey	1 white	1 white	1 white
External equipment	Right-hinged, reversible door	•	•		
	Right-hinged glass door			•	•
	Door lock	•	•	•	•
	Integrated door handle		•	•	•
	Digital temperature display	•	•	•	•
	Legs (4 of) H=100/130 mm	•	•	•	•
	Left hinged door	0	0	0	0
	Castors (4 of) H=125 mm	0	0	0	0
	Marine legs (4 of) H=130/200 mm	0	0	0	0
	Wall suspension	0	0	0	0
Internal equipment	Internal lighting (LED)			•	•
	Additional wire shelves	0	0	0	0
	Stainless shelves Marine shelves		0	0	0
			0	0	0
	Inclined shelves	0	0	0	0
	Wire basket	0	0	0	0
	60 Hz compressor	0	0	0	0

GRAM COMPACT 310 Freezers, height 130 cm						
Product type		F 310 R	F 310 L			
Temperature range		-22/-5	-22/-5			
Refrigeration system		Ventilated Ventilated				
Defrost		Automatic	Automatic			
Finish/equipment		like refrigerators (K 310) - see table above				
Ext./int. equipment		like refrigerators (K 3	10) - see table above			



### Everything within reach

The Compact 310 is designed to fit in where other cabinets are either too small or too large. With a height of 130 cm everything is within reach, offering a positive alternative planning option within a busy kitchen.

Additionally, the "table top" of the cabinet is an ideal location for a piece of equipment such as a microwave oven, offering just the right ergonomic working height.

Internal temperature stability is exceptional thanks to the Gram air distribution system. This means the Compact 310 cabinet maintains a correct and uniform temperature throughout. See illustration page 7.

Cabinets are available in stainless or white finish, with solid door. Refrigerators are also available with glass door. Stainless cabinets with a solid

door are designed with a durable grey inner lining with matching grey wire shelves. White finish solid door cabinets have a white interior with matching wire shelves.

Stainless steel and white refrigerators with glass doors have a white inner lining with matching white wire shelves for optimal light effect display of the stored products inside the cabinet.

The list of equipment is long and includes, a ventilated air distribution system, automatic defrost with re-evaporation of defrost water, digital temperature display, door lock, wire baskets, marine equipment, 60 Hz compressor and suspension kit for wall hanging.





### Wall mounted cabinet

With a wall-mounted Compact 410 cabinet, floor cleaning in restaurant kitchens has become Childs play! In addition it helps the caterer ensure that moisture and dirt will not easily find its way into the cabinet.



### "Side-by-side" combination

Compact 410 cabinets can be placed side-by-side. Dimensions including legs (W x D x H): 119 x 64 x 187,5 cm



Energy consumption kWh/24h

K 410

0,60

Energy Efficiency Index (kWh/48h/m3)

K 410

### COMPACT K 410

- is detailed on the Energy Technology List. Visit the ETL website www.eca.gov.uk/etl

● = Standard equipment | ○ = Optional equipment

GRAM COMPACT 410 Refrigerators, height 187,5 cm					
Product type		K 410 R	K 410 L	KG 410 R	KG 410 L
Temperature range		+2/+12	+2/+12	+2/+12	+2/+12
Refrigeration system		Ventilated	Ventilated	Ventilated	Ventilated
Defrost		Automatic	Automatic	Automatic	Automatic
Finish	External	Stainless	White	Stainless	White
	Internal	Grey ABS	White ABS	White ABS	White ABS
Fittings	Wire shelves (486 x 433 mm)	5 grey	5 white	5 white	5 white
	Wire shelves (486 x 300 mm)	1 grey	1 white	1 white	1 white
External equipment	Right-hinged, reversible door	•	•		
	Right-hinged glass door			•	•
	Door lock	•	•	•	•
	Integrated door handle		•	•	•
	Digital temperature display	•	•	•	•
	Legs (4 of) H=100/130 mm	•	•	•	•
	Left-hinged door	0	0	0	0
	Castors (4 of) H=125 mm	0	0	0	0
	Marine legs (4 of) H=130/200 mm	0	0	0	0
	Wall suspension	0	0	0	0
Internal equipment	Internal lighting (LED)			•	•
	Additional wire shelves	0	0	0	0
	Stainless shelves		0	0	0
Marine shelves		$\circ$	0	0	0
	Inclined shelves	0	0	0	0
	Wire basket	0	0	0	0
	60 Hz compressor	0	0	0	0

GRAM COMPACT 410 Freezers, height 187,5 cm						
Product type		F 410 R	F 410 L			
Temperature range		-22/-5 -22/-5				
Refrigeration system		Ventilated Ventilated				
Defrost		Automatic Automatic				
Finish/fittings		like refrigerators (K 410) - see table above				
Ext./int. equipment		like refrigerators (K 410) - see table above				



# A compact choice with exceptional capacity

The Compact 410 models are versatile refrigerators and freezers designed for storing products in commercial workplaces. The cabinets are spacious, despite being only 60 cm wide and 64 cm deep.

Internal temperature stability is exceptional thanks to the Gram air distribution system. This means the Compact 410 cabinet maintains a correct and uniform temperature throughout. See illustration page 7.

Cabinets are available in stainless or white finish with solid door. Refrigerators are also available with glass door. Stainless cabinets with solid door are designed with a durable grey inner lining with matching grey wire shelves. White finish solid

door cabinets have a white interior with matching wire shelves. Both stainless steel and white refrigerators with glass door are with white inner lining with matching white wire shelves to have optimal light effect and display of the stored products inside the cabinet.

The list of equipment is long and includes, among other things, a ventilated air distribution system, automatic defrost with re-evaporation of defrost water, digital temperature display, door lock, wire baskets, inclined shelves (for wine bottles), marine equipment, 60 Hz compressor and suspension kit for wall hanging.









Energy consumption kWh/24h

K 610	0,90
F 610	3.40

Energy Efficiency Index (kWh/48h/m3)

K 610	6,40
F 610	32,65

### Robust construction, high specification

The inside of the door, shelf supports and wall rails are stainless steel.

### Easy maintenance and service

There is easy access to the replacable dust and grease filters. The compressor and refrigeration system is housed in the unique easy to service Gram plug-in unit.

### COMPACT K and F 610

 are detailed on the Energy Technology List. Visit the ETL website www.eca.gov.uk/etl



2/1 GN

● = Standard Equipment | ○ = Optional Equipment

	GRAM COMPACT 610 Re	frigerators,	height 201	cm	
Product type		K 610 R	K 610 L	KG 610 R	KG 610 L
Temperature range		+2/+12	+2/+12	+2/+12	+2/+12
Extended temp. range	Models: M 610 R/L	-5/+12	-5/+12		
Refrigeration system		Ventilated	Ventilated	Ventilated	Ventilated
Defrost		Automatic	Automatic	Automatic	Automatic
Finish	External	Stainless	White	Stainless	White
	Internal	Grey ABS	Grey ABS	Grey ABS	Grey ABS
Fittings	Wire shelves (530 x 650 mm)	4 grey	4 grey	4 grey	4 grey
External equipment	Right-hinged, reversible door	•	•		
	Right-hinged glass door			•	•
	Door lock	•	•	•	•
	Integrated door handle	•	•	•	•
	Digital temperature display		•	•	•
	Legs (4 of) H=130/200 mm	•	•	•	•
	Left-hinged door	0	0	0	0
	Castors (4 of) H=125 mm	0	0	0	0
	Marine legs (4 of) H=130/200 mm	0	0	0	0
Internal equipment	Internal lighting (LED)			•	•
	Additional wire shelves	0	0	0	0
	Stainless shelves	0	0	0	0
	Marine shelves	0	0	0	0
	60 Hz compressor	0		0	0

GRAM COMPACT 610 Freezers, height 201 cm						
Product type		F 610 R	F 610 L			
Temperature range		-25/-5 -25/-5				
Refrigeration system		Ventilated Ventilated				
Defrost		Automatic Automatic				
Finish/fittings	lik	like refrigerators (K 610) - see table above				
Ext./int. equipment	lik	ce refrigerators (K 6	10) - see table above			



## Many virtues, few limitations...

The robust construction of the Compact 610 recognises the demands of the working professional kitchen. Internal temperature stability is exceptional thanks to the Gram air distribution system. This means the Compact 610 cabinet maintains a correct and uniform temperature throughout.

See illustration page 7.

The Compact 610 range are spacious 2/1 GN cabinets available either as a refrigerator or freezer in stainless or white finish with solid door or glass door (only refrigerator with glass door). Dimensions (W x D x H):  $70 \times 87 \times 201$  cm.

The cabinets are designed with a durable one piece easy to clean moulded grey ABS inner lining. The external front and side walls are in stainless or white finish, inside of the door, shelf supports and wall rails are stainless steel. The adjustable legs facilitate cleaning beneath the cabinets.

The list of equipment includes, among other things, a ventilated air distribution system, automatic defrosting with re-evaporation of defrost water, digital temperature display, door lock, marine equipment and a 60 Hz compressor.









Qualified for Energy Technology List Physics and State Control Technology List Physics	GRA	GRA			
Authorised User No. 00114		Refrigerators		Freezers	Refrigo
Product type		K 210	KG 210	F 210	K 310
Temperature range	°C	+2/+12	+2/+12	-22/-5	+2/+12
Refrigeration capacity at -10/+45°C	Watt	154	154	-	154
Refrigeration capacity at -25/+45°C (with closed door)	Watt	-	-	158	-
Energy consumption	kWh/24h	0,5	0,7	1,1	0,6
Added to The Energy Technology List		-			
Connection (3)	V/Hz	230/50			
Connection load	Watt	99	103	125	99
Amperage, running figures	А	0,95	0,97	0,91	0,95
Ambient temperature min./max.	°C		+16/+35		
Insulation (cyklopentane)	mm		50		
Refrigerant (isobutane/propane) (1) (2)			R600 a		
Volume, gross	I		125		
Volume, net	I		104		
WxD	mm		595 x 640		
H (feet)	mm		830		
H (legs)	mm		900		
H (castors)	mm		925		
Diagonal (310, 410 and 610 on legs)	mm		1050		
Weight, gross	kg	46	52	46	61
Sound level	dB(A)	36,5	35,0	39,7	(4)

<sup>(1)</sup> Refrigerators available with refrigerant R134a

<sup>(2)</sup> Freezers available with refrigerant R404A

<sup>(3) 230</sup>V/60 Hz compressor available (optional)

<sup>(4)</sup> This information was not available at the time this brochure was printed





310	GRAM COMPACT 410			GRAM COMPACT 610		610	
Freezers	Refrige	erators	Freezers	Refrigerators Freezo			Freezers
F 310 R	K 410	KG 410	F 410	K 610	M 610	KG 610	F 610
-22/-5	+2/+12	+2/+12	-22/-5	+2/+12	-5/+12	+2/+12	-25/-5
-	207	307	-	354	354	354	-
204	-	-	212	-	-	-	512
1,6	0,6	1,1	1,6	0,9	0,9	(4)	3,4
	$\checkmark$			$\checkmark$			$\checkmark$
		230/50			23	30/50	
141	113	117	147	241	241	300	435
1,01	0,83	1,16	0,98	1,50	1,50	1,59	2,48
	+16/+35				+1	6/+35	
	50					60	
		R600 a			R	600 a	R290
	346					583	
	312					513	
		595 x 640			695	x 868	
		-		-			
	1875			2010			
	1900			2000			
	1981			2189			
62	75	84	78	111	111	122	114
(4)	35,1	36,3	38,6	44,2	44,2	(4)	48,63
	Freezers F 310 R -22/-5 - 204 1,6 - 141 1,01	Freezers Refrige F 310 R K 410 -22/-5 +2/+12 - 207 204 - 1,6 0,6 - √  141 113 1,01 0,83	Freezers         Refrigerators           F 310 R         K 410         KG 410           -22/-5         +2/+12         +2/+12           -         207         307           204         -         -           1,6         0,6         1,1           -         230/50           141         113         117           1,01         0,83         1,16           +16/+35         50         R600 a           346         312           595 x 640         -           1875         1900           1981         62         75         84	Freezers         Refrigerators         Freezers           F 310 R         K 410         KG 410         F 410           -22/-5         +2/+12         +2/+12         -22/-5           -         207         307         -           204         -         -         212           1,6         0,6         1,1         1,6           -         230/50         -         -           141         113         117         147           1,01         0,83         1,16         0,98           +16/+35         50         -           R600 a         346         312           595 x 640         -         -           1875         1900         -           1981         62         75         84         78	Freezers         Refrigerators         Freezers         Ref           F 310 R         K 410         KG 410         F 410         K 610           -22/-5         +2/+12         +2/+12         -22/-5         +2/+12           -         207         307         -         354           204         -         -         212         -           1,6         0,6         1,1         1,6         0,9           -         -         -         -         ✓           230/50         -         -         ✓           141         113         117         147         241           1,01         0,83         1,16         0,98         1,50           +16/+35         50         -         -           R600 a         346         -         -           312         -         -         -           595 x 640         -         -         -           1900         -         -         -           1900         -         -         -           1900         -         -         -           1900         -         -         - <t< td=""><td>Freezers         Refrigerators         Freezers         Refrigerators           F 310 R         K 410         KG 410         F 410         K 610         M 610           -22/-5         +2/+12         +2/+12         -22/-5         +2/+12         -5/+12           -         207         307         -         354         354           204         -         -         212         -         -           1,6         0,6         1,1         1,6         0,9         0,9           -         -         -         -         -         -           230/50         23         -         -         -         -           230/50         23         -</td><td>Freezers         Refrigerators         Freezers         Refrigerators           F 310 R         K 410         KG 410         F 410         K 610         M 610         KG 610           -22/-5         +2/+12         +2/+12         -22/-5         +2/+12         -5/+12         +2/+12         +2/+12           -         207         307         -         354         354         354           204         -         -         212         -         -         -           1,6         0,6         1,1         1,6         0,9         0,9         (4)           -         -         -         -         -         -         -           230/50         230/50         230/50         230/50         -         -         -           141         113         117         147         241         241         300         1,59         +16/+35         +16/+35         +16/+35         50         60         60         60         60         8600 a         8600 a         8600 a         695 x 868         -         -         -         -         -         -         -         -         -         -         -         -         -</td></t<>	Freezers         Refrigerators         Freezers         Refrigerators           F 310 R         K 410         KG 410         F 410         K 610         M 610           -22/-5         +2/+12         +2/+12         -22/-5         +2/+12         -5/+12           -         207         307         -         354         354           204         -         -         212         -         -           1,6         0,6         1,1         1,6         0,9         0,9           -         -         -         -         -         -           230/50         23         -         -         -         -           230/50         23         -	Freezers         Refrigerators         Freezers         Refrigerators           F 310 R         K 410         KG 410         F 410         K 610         M 610         KG 610           -22/-5         +2/+12         +2/+12         -22/-5         +2/+12         -5/+12         +2/+12         +2/+12           -         207         307         -         354         354         354           204         -         -         212         -         -         -           1,6         0,6         1,1         1,6         0,9         0,9         (4)           -         -         -         -         -         -         -           230/50         230/50         230/50         230/50         -         -         -           141         113         117         147         241         241         300         1,59         +16/+35         +16/+35         +16/+35         50         60         60         60         60         8600 a         8600 a         8600 a         695 x 868         -         -         -         -         -         -         -         -         -         -         -         -         -

COMPACT GBX 06-2014





Innovative and functional food storage







Gram Commercial A/S Aage Grams Vej 1 DK-6500 Vojens

Tel: +45 73 20 12 20 Fax: +45 73 20 12 01 e-mail: info@gram-commercial.com

www.gram-commercial.com

Dealer:



#### Facts about us

Gram Commercial A/S develops and produces refrigerators and freezers for commercial kitchens. With our head office in Vojens, Denmark, we are part of the Japanese owned Hoshizaki Group, a global supplier of equipment for professional kitchens. With an extensive sales and service network around the world, we provide expert local service to our customers wherever you are.