

ONYX TECHNICAL DATASHEET



| | CPC2 | | CPC3 | | CPC4 | | CPC5 | |
|---------------------|------------|----------|----------|----------|----------|----------|----------|-----------|
| Dimensions (mm) | External | Internal | External | Internal | External | Internal | External | Internal |
| Width | 955 | 854 | 1420 | 1320 | 1885 | 1785 | 2350 | 2250 |
| Depth | 860 | 583 | 860 | 583 | 860 | 583 | 860 | 583 |
| Height | 1100 | 647 | 1100 | 647 | 1100 | 647 | 1100 | 647 |
| Door Opening | | 392 | | 392 | | 392 | | 392 |
| Capacity | cu.ft/ltrs | | | | | | | |
| Capacity cu.ft/ltrs | | 12.5/355 | | 21.6/613 | | 29.2/828 | | 36.8/1043 |

KEY FEATURES

- Foodsafe stainless steel exterior and interior
- CoolSmart controller
- Designed and engineered to operate efficiently up to a 43°C ambient
- Self closing doors
- Precision injected, high density 75mm polyurethane insulation. Provides excellent thermal efficiency with low GWP (Global Warming Potential) and zero ODP (Ozone Depletion Potential)
- Heavy duty, non-marking swivel castors with brakes
- Barrel locked doors
- High performance, efficient commercial refrigeration system
- Unique air flow design with protective 1°C air curtain
- Removable, easy to clean crumb tray and lift off night cover
- Removable internal fittings including racking and shelf supports
- Connection to third party supervisory communication systems such as BMS is possible using proprietary equipment. Please contact Williams for more information.

OPTIONS

- Bank of 2 drawers
- Hinged cover
- Granite worktop
- Polypropylene worktop
- 1/3 x 150mm Gastronorm pans with lids
- Stainless steel back



ONYX TECHNICAL DATA

| | CPC2 | CPC3 | CPC4 | CPC5 |
|-------------------|-------------------|-------------------|-------------------|-------------------|
| Temperature (°C) | +1/+4°C | +1/+4°C | +1/+4°C | +1/+4°C |
| Power Supply | 230V/50Hz/1Ph | 230V/50Hz/1Ph | 230V/50Hz/1Ph | 230V/50Hz/1Ph |
| Fuse (Amps) | 13 | 13 | 13 | 13 |
| Defrost | Automatic Hot Gas | Automatic Hot Gas | Automatic Hot Gas | Automatic Hot Gas |
| Noise level (dBA) | 67 | 64 | 64 | 68 |

Fittings

| | | | | |
|----------------------------|---|---|----|----|
| Shelves | 4 | 6 | 8 | 10 |
| Trayslides per door | 4 | 4 | 4 | 4 |
| 1/3 GN Pans (not included) | 4 | 7 | 10 | 12 |

Electrical / Energy Data - Standard Refrigerant

| | | | | |
|-------------------------|------|------|------|------|
| Refrigerant | R290 | R290 | R290 | R290 |
| Start Up (Amps) | 16 | 21 | 21 | 28 |
| Running (Amps) | 2.88 | 4.04 | 4.53 | 4.68 |
| Heat Rejection (Watts)* | 907 | 1428 | 1428 | 2503 |

IMPORTANT NOTES:

*Evaporating at -10°C in 32°C Ambient

Williams is committed to a policy of continual product development and innovation. As such, we reserve the right to change product specifications stated without prior notice.

Williams Refrigeration
Bryggen Road,
North Lynn Industrial Estate
King's Lynn, Norfolk. PE30 2HZ

T +44(0) 1553 817 000
Spares: +44(0) 1553 817 017
E info@williams-refrigeration.co.uk
W www.williams-refrigeration.co.uk

