

# PROFESSIONAL DISHWASHERS

	TO PLINE			
	CWG520D	CWG520SD	CW521D	CW521SD
Control type	electronic	electronic	electronic	electronic
Basket dimensions (mm)	500x500	500x500	500x500	500x500
Baskets/hour *	60/40/24/15	60/40/24/15	60/40/24/15	60/40/24/15
Programs	7	7	7	7
Glass cycle	•	•	•	•
ULTRA CLEAN PRO cycle	•	•	•	•
Standby function	•	•	•	•
HTR system	•	•	•	•
Soft start	•	•	•	•
Aquastop	-	-	-	-
Automatic tank washing on drain down	•	•	•	•
Filter sensor	•	•	•	•
Wash arms	2 - AISI 304 stainless steel	2 - AISI 304 stainless steel	2 - AISI 304 stainless steel	2 - AISI 304 stainless steel
Rinse arms	2 - AISI 304 stainless steel	2 - AISI 304 stainless steel	2 - AISI 304 stainless steel	2 - AISI 304 stainless steel
Integral water softener	-	•	-	•
DHR heat exchanger	-	-	-	-
Drain system (integrated pump and filter)	•	•	•	•
Rinse pump	•	•	•	•
Thermal-acoustic insulation	door/wash chamber	door/wash chamber	door/wash chamber	door/wash chamber
Insulated boiler	•	•	•	•
Double skinned tank	•	•	•	•
Double skinned door	•	•	•	•
Rinse aid dispenser	peristaltic	peristaltic	peristaltic	peristaltic
Detergent dispenser	peristaltic	peristaltic	peristaltic	peristaltic
Doing Control	electronic	electronic	electronic	electronic
Non-return valve	•	•	•	•
WRAS approved	N / A	N / A	•	•
Useable loading height (mm)	415	415	415	415
Baskets provided	1 x WB50G01 1 x WB50G02 1 x PHOOS02	1 x WB50G01 1 x WB50G02 1 x PHOOS02	1 x PB50D01 1 x PB50G01 1 x PHOOS02	1 x PB50D01 1 x PB50G01 1 x PHOOS02
Wash tank capacity (l)	11	11	11	11
Boiler capacity (l)	6	6	6	6
Rinse water consumption per cycle (litres)	2.7	2.7	2.7	2.7
Power supply/ Electrical connection / Total power installed	400V 50 Hz 3N/ 5.7 kW 230V 50Hz 1N/ 5.7 kW* 230V 50Hz 1N/ 4.0 kW 230V 50Hz 1N/2.4 kW	400V 50 Hz 3N/ 5.7 kW 230V 50Hz 1N/ 5.7 kW* 230V 50Hz 1N/ 4.0 kW 230V 50Hz 1N/2.4 kW	400V 50 Hz 3N/ 5.7 kW 230V 50Hz 1N/ 5.7 kW* 230V 50Hz 1N/ 4.0 kW 230V 50Hz 1N/2.4 kW	400V 50 Hz 3N/ 5.7 kW 230V 50Hz 1N/ 5.7 kW* 230V 50Hz 1N/ 4.0 kW 230V 50Hz 1N/2.4 kW
Boiler heating element (kW)	5	5	5	5
Tank heating element (kW)	0.8	0.8	0.8	0.8
Wash pump (kW)	0.7	0.7	0.7	0.7
Outside dimensions WxDxH (mm)	600x600x820	600x600x820	600x600x820	600x600x820
Min/max inlet water pressure (bar)	1 - 6	1 - 6	1 - 6	1 - 6
Weight (kg - net / gross)	65/73	68/76	65/73	68/76

\* default factory setting

## REVERSE OSMOSIS TREATMENT UNITS

WO-01	WO-04	WO-03	WO-02
40	40	40	40
150 **	80 /120 **	60 / 80 **	100 **
30	24 ***	18 ***	-
30	30	30	30
1.5 /6	1.5 /6	1.5 /6	1.5 /6
-	-	-	-
•	•	•	-
-	-	-	-
5-30 **	5-30 **	5-30 **	5-30 **
Active carbon filters	Active carbon filters	Active carbon filters	Active carbon filters
376x600x814	300x462x688	275x500x460	424x120x472
230V, 50Hz single-phase / 0.45	230V, 50Hz single-phase / 0.25	230V, 50Hz monofase / 0.15	230V, 50Hz single-phase / 0.15