





Model:

Model featured - DY822







Telephone Helpline: 0845 146 2887



Safety Tips

Whilst all care has been taken to remove sharp edges, care must be taken when cleaning or handling the sink to prevent risk of injury from exposed metal edges.

Do not overload the sink top or shelf causing it to bend.

Product Description

- DY820 Vogue St/St Single Bowl Sink R/H Drainer - 1000mm
- DY821 Vogue St/St Single Bowl Sink L/H Drainer - 1000mm
- DY822 Vogue St/St Single Bowl Sink L/H Drainer - 1200mm
- DY823 Vogue St/St Single Bowl Sink R/H Drainer - 1200mm
- DY824 Vogue St/St Double Bowl Sink R/H Drainer - 1500mm

- DY825 Vogue St/St Double Bowl Sink L/H Drainer - 1500mm
- DY826 Vogue St/St Single Bowl Sink Double Drainer - 1500mm
- DY827 Vogue St/St Double Bowl Sink R/H Drainer - 1800mm
- DY828 Vogue Double Bowl Sink L/H Drainer -1800mm
- DY829 Vogue Double Bowl Sink Double Drainer - 2100mm

Assembly



Note: Be sure to check all packaging materials for any small parts that may have come loose during transportation.

- Remove all protective film from the shelf, legs and underneath the sink, taking care to avoid scratching the surfaces.
- 2. Place the sink face down on the floor [A].
- 3. Insert the legs into the sockets situated at each corner of the sink [B & C].



Note: Do not secure the legs to the sink at this stage. This makes inserting the shelf easier.

 Position the corner sockets of the shelf over the four legs and lower the shelf approximately 25cm down the legs [D].



Note: The legs are marked at 25cm to help position the shelf in a level position.

5. Hold the shelf in position and insert the grub screws to loosely secure the shelf to each leg [**E**] and the legs to the sink top.



Note: Leaving the grub screws loose allows for adjustments to sink shelf and legs.

- 6. Adjust the shelf and legs so that they are level (use a spirit level if required).
- 7. Tighten all the grub screws [**F**].
- 8. Stand the sink upright and remove the remaining protective film [G].
- 9. If necessary adjust the feet to level the sink.




Cleaning

- Before using for the first time the sink should be cleaned thoroughly.
- Clean the sink regularly using a cleaning agent suitable for use with stainless steel.
- Always remove cleaning agent residue. This can discolour the surface of the shelf.
- Never leave the shelf surface damp as this can cause discolouration.
- Regularly remove and clean the sink drainer unit to avoid potential damage and blockages.

Drainer Unit

Number	Description
1	Overflow Pipe
2	Ø70 Drainer Body
3	Ø67.3 Washer
4	Ø70 Washer
5	Ø69.6 Hexagonal cap



- 1. Insert Drainer unit as shown above.
- 2. Connect the unit to the drain outlet with suitable pipework.



Note: Consult a qualified plumber if unsure of suitable connections.

All rights reserved. No part of these instructions may be produced or transmitted in any form or by any means, electronic, mechanical, photocopying, recording or otherwise, without the prior written permission of VOGUE.

Every effort is made to ensure all details are correct at the time of going to press, however, VOGUE reserve the right to change specifications without notice.

