## **DOMINATOR BOILING PANS**

### E2078 - 45, 90 and 135 litre





#### **MODELS and ACCESSORIES**

**E2078-45** Boiling pan (45 litre) **E2078-90** Boiling pan (90 litre) **E2078-135** Boiling pan (135 litre)

• Lift-out pan kit

#### **KEY FEATURES**

- Choice of capacity
  - available as option of of single and dual purpose
- Operational controllability
  - gentle boil or fast simmer with variable control
- Easy to fill and empty
  - swivel tap and large draw-off fitted as standard
- Simple to keep clean
  - one piece stainless steel hob and pan
- Operator safety
  - lift-off lid directs steam away from user

#### **INSTALLATION NOTES**

Adequate ventilation must be provided to supply sufficient fresh air to allow easy removal of any such products that may present a risk to health. Please consult current legislation for details that relate to specific locations.

Install unit on a level, fireproof surface in a well-lit, draught free position. If floor is made of a combustible material, local fire requirements must be checked to ensure compliance.

A clearance of 150mm should be observed between appliance and any combustible wall.








# **DOMINATOR BOILING PANS**

E2078 - 45, 90 and 135 litre

## **MODEL DIMENSIONS** (in mm)







Dim	E2078-45	E2078-90	E2078-135
Α	Ø610	Ø730	Ø826
В	838	838	864
С	Ø432	Ø552	Ø648
D	394	514	606
E	398	518	566
F	108	108	110
G	52	52	62
Н	194	194	178
J	800	870	940
K	230	230	330
L	45	45	45
М	745	745	960

#### **SPECIFICATION DETAILS**

	E2078-45	E2078-90	E2078-135
Total rating (kW)	6.7	11	13.9
Electrical supply voltage	400-415V 3N~ or 230-240V~	400-415V 3N~ or 230-240V~	400-415V 3N~ or 230-240V~
Electrical current split (amps)	L1-11.5A/L2-8.5A/L3-8.5A	L1-14.7A/L2-17.5A/L3-17.5A	L1-17.5A/L2-20.8A/L3-20.8A
Capacity (litres)	45	90	135
Water inlet	1/2" BSP	1/2" BSP	1/2" BSP
Weight (kg)	86	122	145
Packed weight (kg)	97	132	155

