

E8 OD

COMPAK

Innovation intersects tradition

Direct access to the grinding chamber for cleaning or burr replacement without losing the adjustment. **Lock Load System** optional. Micrometric **Parallel System** adjustment.

Burrs durability: 800 Kg*. Made of **high-durability tempered steel K110**. Optional **Red Speed** burrs available.







Motor **630 W**
Burrs **Ø 83 mm**

KEY SPECIFICATIONS 230 V/50 Hz








Motor output	630	W
Revolutions per minute	1.290	rpm
Ø Burrs	83	mm
Espresso point production*	4,2	g/s
Hopper capacity	1.250	g
Height x width x depth	600 x 230 x 385	mm
Net weight	15,36	kg

* Production and durability based on a medium roast coffee and grinding point for Espresso. There is a direct relation between the wear of the burrs and the increase in time per dose

KEY FEATURES

-  Micrometric **Parallel System** adjustment
-  **Direct access** to the grinding chamber (LLS optional)
-  **Coffee outlet illuminated** with LEDs
-  **Motor with fan**
-  **Adjustable fork** in height and depth
-  Front-mounted **refill button**

ELECTRONIC FEATURES

-  **2.8" TFT touchscreen**
-  **Multilanguage** display
-  **Portafilter detector** (optional)
-  **Menu access** protection **with password**
-  Dose counter, both **absolute and relative**
-  **Wear and changing burrs** alarm
-  **Screensaver**

