

**PRODUCT OPTIONS AND ACCESSORIES**

- DP10 DESCALER POWDER
- BR55 EB3FX AND EB4FX WALL BRACKET
- FC04 EBFX WATER FILTER - FROM 2015
- EBHF01 Lincat EB Hands Free Tap Adaptor

Efficient both in its use of space and in its use of energy, the high-powered FilterFlow Automatic Water Boiler is perfect for busy staff rooms and anywhere where employees have to wait for the kettle to boil. Providing hot water on tap 24/7, the boiler also comes with a filtration system built-in to improve water quality. You can modify the settings via the clever colour touchscreen display, while the boiler is designed to save energy via its eco mode which learns usage patterns and switches to 50% volume.

PRODUCT FEATURES

- Narrow 250mm footprint saves valuable counter space without compromising capacity or performance
- Built-in water filtration system improves water quality and reduces scale build-up. High volume, easy change FilterFlow cartridge
- Easily operated from a large, colour touchscreen display. Menu navigation is quick and easy with the temperature and timer simple to adjust
- Eco setting reduces the volume of boiling water by 50% for quieter periods. The intelligent predictive eco setting learns usage patterns and switches between eco mode and standard mode to deliver the required hot water output in the most economical way
- 7-day timer allows the boiler to be programmed to switch off overnight or at weekends to conserve energy
- Enhanced diagnostics identify possible causes. The on screen diagnostic information will enable the engineer to identify the parts needed and repair your water boiler at first visit

WEIGHTS & DIMENSIONS		SHIPPING DETAILS	
Width	250 mil	Ship Width	69.5 cm
Depth	525 mil	Ship Depth	36.6 cm
Height	596 mil	Ship Height	53 cm
Weight	13.4 kg	Ship Weight	14.74 kg
		Ship Method	Small Parcel (FedEx, UPS, DHL)
		Shipping Package Type	Pieces
		Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
		Quick Ship Product	No
WATER, PLUMBING, AND DRAINAGE Specs			
Water Line Required	Yes	PRODUCT CERTIFICATIONS	
Water Connection Source Type	Water Main	IP23 UK CA 	
Water Inlet Size	0.75 in		
Water Inlet Pressure	6 Bar		
Drain Line Required	No		
ENERGY Specs			
Primary Energy Type	Electric	Electrical Plug Type	UK 3-Pin Plug
Electrical Total Amperage	13 A	Number of Electrical Plugs	1
Electrical Volts	230V	Electrical Connection Type	Cord and Plug
Electrical Total Wattage	3000 W	Number of Electrical Conductor Wires	1
Electrical Kilowatts	3 kW	Dedicated Circuit Required	No
Electrical Phase	1-Phase	Electrical Remarks	Single
ADDITIONAL SPECIFICATIONS			
Capacity (Volume)	15 l	Rapid Draw Off Hot	11 l
Construction Materials	Stainless Steel	Rapid Draw Off Hot Cups	55 C
Control Type	Electronic	Ventless Cooking Technology	No
Hourly Hot Water Output	31 l	Temperature Maximum	98 °C
Hourly Number of Hot Cups	155	Temperature Minimum	70 °C
BIDDING SPECIFICATIONS (SHORT FORM Specs)			
Bidding Specifications Not Available.			

TECHNICAL DRAWING