



F79/010 - IMC WasteStation Macerator and Dewaterer - with Airbreak

Reliable, efficient, safe and easy to operate, the WasteStation allows operators to quickly and effectively remove waste, creating a safer and cleaner kitchen.

- ✓ **A solution for your business** - process up to 700 kg waste per hour, the equivalent of 1450 covers
- ✓ **Transport savings** - reduce waste collection costs by up to 80% by reducing the food waste volume and weight requiring collection
- ✓ **Storage savings** - by reducing the waste volume, on site waste storage facility requirements are also reduced
- ✓ **Labour savings** - reduce staff time processing and managing waste, fast efficient disposal of food waste as and when you need to, with no schedule
- ✓ Self-cleaning operation - WasteStation can undertake a thorough clean, ensuring the whole system is free of food and grease
- ✓ Self-emptying - eliminates the need for staff to empty the auger assembly, reducing labour times required to operate the machine. Intelligent electronic sensor detects when the bin is full
- ✓ Visual control panel - kitchens are a noisy environment, so WasteStation incorporates a simple LED display to allow monitoring of the state of the equipment during operation
- ✓ **Energy savings** - compact design and short processing times ensure low operating costs and minimal use of kitchen floor space
- ✓ **Maximise kitchen hygiene** - fully enclosed system prevents food entering the unit, keeping the machine clean and free of waste, and reducing operational noise. Following each operation, the machine undertakes a quick self-rinse cycle, preventing any build-up of food
- ✓ With airbreak

Specifications

Summary

Brand	IMC
Range	WasteStation
Power Type	Electric
Unit Type	Free-standing
Available in UK Only	No
UK Warranty	2 Years Parts and Labour Warranty
Export Warranty	Contact your local dealer
Mounting	Free-standing
GTIN	5056105197034

Power and Performance

Total Power kW	4.1
HP	5.5
IP Rating	IP55
Operating Decibels	83

Key Specifications

Airbreak	Yes
Manual or Auger Feed	Manual
Self Cleaning	Yes

Capacity

Type of Waste	Tough waste
Covers Per Sitting	1450
Capacity Kg per Hour	700

Weights and Dimensions

Unit Height (External) mm	1000
Unit Width (External) mm	900
Unit Depth (External) mm	700
Net Weight Kg	192

Supply Connections

Requires Installation	Yes
Requires Electrical Supply	Yes
UK 3 Pin Plug	No
16A Commando Plug	No
Requires Hardwiring	Yes
Electrical Supply Rating Watts	4,100
Three Phase Amps	8.62
Three Phase Voltage	380-415
Water Supplied From	Mains Fed
Water Connection Pressure Bar	Head of water not less than 0.18 bar
Drain Connection	2" waste drain
Water Connection	3/4" BSP
Water Consumption Litres/min	12

Shipping

Packed Weight Kg	295
Packed Height cm	152
Packed Width cm	90
Packed Depth cm	115

Available Accessories

A13/125	Waste Scraper for WasteStation
K12/357	Waste Caddy for WasteStation and WastePro II



Lincat Limited

Whisby Road,
Lincoln, LN6 3QZ,
United Kingdom

Company No: 2175448

A member company of



Customer Care

Tel: +44 1522 875500
Email: care@lincat.co.uk

Export Customers

Tel: +44 1522 875536
Email: export@lincat.co.uk

Opening Hours

Monday – Friday:
8.30am – 5pm