



ECO MIDI F 82 RAG 4N

Product series: Superior - Eco

Item number: 962820241



The GRAM ECO MIDI F 82 RAG 4N is with a net internal volume of 459 Ltr.

The ECO series gained enormous popularity among our customers across all segments of the hospitality and foodservice industry.

One of the reasons is the wide span of models for different usage areas and purposes. The series can accommodate diverse and specific needs when it comes to functionalities, capacities, and kitchen designs. At the same time, ECO cabinets do not compromise on energy efficiency and low running costs

Food Safety

The efficient air circulation system helps to maintain perfect storage temperatures. Designed to recover the inside temperature rapidly after each door opening. Temperatures for optimal food safety and enhanced shelf-life are maintained for climate class 5.

Low Running Costs

Tracking and controlling the lifetime costs of equipment is key to any successful professional kitchen. All ECO cabinets strike with excellent energy ratings and help you save running costs on a daily level. The Energy Efficiency Class of the ECO MIDI F 82 RAG 4N is C.

Comfortable Work Environment

The ECO range contributes to a healthier work environment with low noise levels of approximately 45 dB(A) when the compressor is running.

Hygiene & Ergonomic Design

Thanks to the rounded corners and smooth surface, frequented cleaning routines become a quick and simple task. All Cabinets have self-closing doors with full-height handles providing easy access for cleaning. The patented pedal door opener can be placed on the left or right side.

Smart Design

The ECO series strikes with its energy efficiency, food-safe design, and smart extras such as the patented pedal door opener. This helpful feature can be placed on the left or right side. While carrying goods, the cabinet door can be opened with a quick foot tap.

SPECIFICATIONS

Temperature range	-25/-5°C
Volume, gross (l)	603
Net usable volume (l)	459
Interior	Stainless, aluminium
Dimensions W x D x H (mm)	820 x 775 x 2000
Weight, packed (kg)	139
Refrigerant	R290
GWP	3
Connection	230V, 50 Hz
Connection load (Watt)	398
Energy consumption Ecodesign AEC (kWh)	1807
Energy Efficiency Class	C

Energy Efficiency Index EEI	48.4
Sound level – dB(A)	48.5
Insulation (mm)	70 mm (cyclopentane)
Refrigeration capacity at -25°C (Watt)	499
Climate class	5
GN – Shelf size	2/1 GN wide
Door Type	Solid Door
Exterior	Vario Silver
Refrigerant (kg)	0.1
CO2 equivalent (kg)	0.33
Equipped with	Right hand hinged reversible door, automatic door closing, 4 grey shelves, LED lighting