

COMPACT FG220R DR G U

GLASS DOOR FREEZER



ACCESSORIES INCLUDED

1 white shelf (483.8x 433mm) and 1 bottom shelf

OPTIONAL EXTRAS

Shelf, white

Bottom shelf, white

PRODUCT SERIES: COMPACT 220

ITEM NUMBER: 155220030

COUNTRY OF ORIGIN: INDIA

COMPACT K 220 models not only comply with the EU Ecodesign labelling regulation, but ranking in the energy efficiency class A+ these refrigerators offer the most energy efficient compact models in the marketplace.

Correct and uniform temperature throughout the cabinet is critically important for a food storage cabinet. GRAM COMPACT provides this with a unique ventilated air distribution system and a robust refrigeration system with sufficient refrigeration capacity.

COMPACT K 220 is approved to endure up to 30°C ambient temperature (Climate class 4). It further offers low heat emission with minimal compressor running time.

Compact 220 models are designed to fit under worktops in commercial workplaces. With their width of 59.5cm, depth of 64.2cm and height of just 83cm, these cabinets are ideal for building in beneath worktops. As a free-standing cabinet the undercounter COMPACT 220 provides extra work space with its "table top".

Materials Exterior: Stainless

Materials Interior: White polystyrene (PS) lining.

Gross volume: 128 ltr

- Air circulation system
- Right hand hinged door. Left hand door available on request
- Reversible door (including glass doors)
- Door lock
- Internal LED light (glass door models)

WARRANTY PERIOD
5 Years on Parts & Labour

EXTERIOR
Stainless Steel AISI 430

INTERIOR
White Finish

Refrigerant type: R600a / Refrigerant: 0.034 kg / CO2 equivalent: 0.102 kg

Energy consumption	Energy efficiency class	Energy efficiency class standard	Energy Efficiency Index (EEI)
906 kWh/year	C	ISO 23953: 2019	21.7 EEI

CERTIFICATIONS



COMPACT FG220R DR G U

TECHNICAL SPECIFICATIONS

Temperature range	Shelf size	Volume, gross	Net usable volume	Power supply	Connection load	Climate class	Sound level	Ref. capacity (at -25 °C)
-19/-5 °C	Shelf 483.8 x 433 mm	123 l	77 l	230V, 50Hz	150 W	3 (maximum ambient temperatures of 25 °C with 60% RH)	39.2 dB(A)	186 W

SHIPPING SPECIFICATIONS

Width (packed)	Depth (packed)	Height (packed)	Volume (packed)	Gross weight	Width	Depth	Height	Net weight
614 mm	720 mm	997 mm	0.441 m3	61 kg	595 mm	667 mm	833 mm	52 kg

Disclaimer: Every effort has been made to ensure that the information contained in this spec sheet is accurate at the time of publishing. Hoshizaki Europe BV assumes no responsibility or liability for typographical errors or omissions or for any misinterpretation of the information within the publication and reserves the right to change without notice.

