



Product Code: FMSLIM1500NG 18-124

1500mm Pro multideck with fully frameless acrylic doors

---



## Features & Benefits

---

- Fully frameless doors can reduce energy consumption by up to 55%
- Add 60mm to depth for spacer if product is to be wall-sited (required for air circulation - detachable if not wall-sited)
- 2x vertical side mounted full length LED lights. On average these last 10x longer than fluorescent lighting and emit a fraction of the heat output.
- Energy saving retracting 'Soft Closing Mechanism' Nightblind.
- Fully removable shelves and supports for ease of cleaning
- Made of high quality food safe superior 'brushed' stainless steel finish for easy wipe-clean efficiency.
- Removable front cover and slide out condensing unit allows easy access for service, minimising down time. Also our After Sales Support is there when you need us: 2 years parts and labour warranty as standard.
- Intelligent controller with easy to read digital display ensures even temperature regulation throughout
- Optimum storage and display from the smallest possible footprint
- Energy saving LED lighting is brighter, lasts longer and saves you money
- Additional shelf depth (400mm) delivers increased volume compared to competitor slimline cabinets

## Refrigeration

R404a - Industry Standard	Standard
Integral Refrigeration System	Standard

## Specification

M2 Temp +2/+4°C	Standard
Width (mm)	1495
Depth (mm)	680
Height (mm)	1780
Unpacked weight (Kgs)	240
Fully Frameless Energy Saving Doors	Standard

## Electrical & Service Data

230/50/1	Standard
Fuse Required (A)	10

## Finish

304 s/s	Standard
---------	----------

## Product Extras

Additional S/S shelf and support brackets	Option
Front wire baskets for additional storage	Option

## Footnotes

- Allow 60mm spacer if product is wall-sited (required for air circulation). Spacers are detachable if product is not to be wall-sited
- Delivery to dealer premises/direct to site on route days free of charge. Delivery and installation to ground floor site as priced - see UK price list for conditions
- Performance complies with the M2 classification as prescribed in EN23953-2:2005, where the M2 classification refers to product temperatures of no greater than +7°C and no lower than -1°C when loaded in accordance with the standard and recorded under the s



Energy



Quality



Value



Design



Hygiene



After Care

Foster Refrigerator, Oldmedow Road, King's Lynn, Norfolk, PE30 4JU

Phone 08432 168800 | Email [sales@foster-uk.com](mailto:sales@foster-uk.com) | Visit [www.fosterrefrigerator.com](http://www.fosterrefrigerator.com)

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.