



Product Code: FMPRO900RF 19-102

900mm Pro multideck with rollershutter



Features & Benefits

- Five display levels maximising capacity
- Energy saving LED lighting is brighter, lasts longer and saves you money
- Additional shelf depth (450mm) delivers increased volume compared to competitor cabinets
- Extra wide glass end panels increase display visibility
- Supplied on roller castors as standard for ease of positioning
- Add 20mm to depth for spacer if product is to be wall-sited (required for air circulation - detachable if not wall-sited)
- 1x top mounted full length LED. On average these last 10x longer than fluorescent lighting and emit a fraction of the heat output.
- Robust lockable security roller shutter with full solid end panels
- Fully removable shelves and supports for ease of cleaning.
- Removable front cover and slide out condensing unit allows easy access for service, minimising down time. Also our After Sales Support is there when you need us: 2 years parts and labour warranty as standard.

External Finish

304 s/s Standard

Electrical, Service & Ecodesign Data

230/50/1 Standard

Fuse Required 13

Internal Finish

304 s/s Standard

Specification

Dimensions (Width) 895

Dimensions (Height) 1995

Dimensions (Depth) 775

Weight (Unpacked, kg) 150

Weight (Packed, kg) 165.9

Depth Note Add 60mm to depth for spacer if product is to be wall-sited required for air circulation - detachable if not wall-sited

Noise DbA @ 1M TBC

Refrigeration

R404a - Industry Standard Standard

Integral Refrigeration System Standard

Footnotes

- Allow 60mm spacer if product is wall-sited (required for air circulation). Spacers are detachable if product is not to be wall-sited
- Delivery to dealer premises/direct to site on route days free of charge. Delivery and installation to ground floor site as priced - see UK price list for conditions



Energy



Quality



Value



Design



Hygiene



After Care