

## Product Code: F3O2 with SB2O5 bin 28–113 320kg output 150kg bin



## Features & Benefits

- · Innovatively designed with new user-friendly electro-mechanical controls to ensure reliability
- The models also incorporate a condenser thermostat, which ensures a full harvest of cubes
- Produces ultra cold square cubes that last longer in the glass, ice bucket and the machine's storage bin
- High output and storage capacity with dedicated storage bins
- The new flush system ensures clear ice free from impurities and eliminates the risk of lime-scale
- Output figures quoted are based on 10°C water input and ambient air temp of 25°C
- Legs provided as standard to increase height for drainage where required 70mm maximum height increase
- 320kg output per 24 hours
- Bin capacity: 150kgs
- Ice: Cubed 24x22x22mm

External Finish		Internal Finish		Refrigeration	
Stainless steel	Standard	N/A	Standard	R134a - Industry Standard	Standard
Electrical, Service & Ecodesign Data		Specification		Drain Rqd Modular	20mm Standard
		Dimensions (Width)	850	Integral Refrigeration System	
230/50/1	Standard	Dimensions (Height)	1670		
Fuse Required	13	Dimensions (Depth)	810		
		Cube - 24 x 22 x 22mm	Standard		
		Noise Dba @ 1M	TBC		
		KG per 24 hours	320		

## Footnotes

• A distance of at least 20cm must be allowed between the sides, back and the walls of the machine



Foster Refrigerator, Oldmedow Road, King's Lynn, Norfolk, PE30 4JU Phone 08432 168800 | Email sales@foster-uk.com | Visit www.fosterrefrigerator.com