



**1** Water

22mm CONNECTION VIA 2 METRE FLEXIBLE HOSE, FEMALE TERMINATION.

WATER SUPPLY 55°C TO 60°C (0°- 3°CLARK MAX) @ 0.5 TO 10.0 BAR MAX. INITIAL TANK FILL 8 LITRES.

RINSE WATER USAGE 1.9 LITRES PER CYCLE. MAX USAGE 110 LITRES PER HOUR.

OUR MACHINES ARE SUPPLIED WITH CLASS 'AA' AIR GAP AS STANDARD.

**2** Drain

DRAIN - 1.75 METRE FLEXIBLE HOSE TO A 40mm TRAPPED STANDPIPE 600mm MAX A.F.F.L.

FLOW RATE 30 LITRES PER MINUTE.

**Other Services**

RINSE AGENT HOSE - 2.5 METRE FLEXIBLE.  
DETERGENT HOSE - 2.5 METRE FLEXIBLE.

**3** Electric

4.6kW 400/50/3 FUSED AT 3 x 16amps. MACHINE SUPPLIED WITH 2.0 METRES OF CABLE  
**CONFIGURABLE TO:**  
5.6kW 230/50/1 FUSED AT 25amps.

**Notes**

APPROX WEIGHTS:  
EMPTY: 50kg's WITH WATER: 64kg's  
\*+40mm