



COMMERCIAL SLICER GL-350

Blade Ø 350 mm.



DYNAMIC PREPARATION
GEAR DRIVEN SLICERS



SPECIFICATIONS

Blade diameter: 350 mm

Cutting capacity

- ✓ Square cut: 250 mm x 250 mm
- ✓ Round cut: 250 mm
- ✓ Rectangular cut: 250 mm x 300 mm

Slice thickness: 0 mm - 15 mm

Carriage run: 320 mm

Total loading: 430 W

IP Protection grade: 43

External dimensions (WxDxH)

- ✓ Width: 800 mm
- ✓ Depth: 580 mm
- ✓ Height: 480 mm

Net weight: 42 Kg

Noise level (1m.): 65 dB(A)

Crated dimensions

840 x 630 x 650 mm

SALES DESCRIPTION

Gear driven slicer.

Gear driven commercial slicer with ring, carriage lock and blade removal tool.

- ✓ Slicer Fully made of high-polished aluminium protected against anodic oxidation.
- ✓ Built-in precision sharpener.
- ✓ Hard-chromed forged scoop knife.
- ✓ Life-lubricated helicoidal gear drive.
- ✓ Easy selection of cutting thickness.
- ✓ Bearing-mounted slide plate.
- ✓ Professional slicer with ring, carriage lock and blade removal tool.
- ✓ Heavy duty, ventilated motor.

Components in contact with food are completely detachable for easier cleaning.

AVAILABLE MODELS

5050064 Slicer GL-350 230-400/50/3

5050070 Slicer GL-350 230/50/1

** Ask for special versions availability*



www.sammic.co.uk

Food Service Equipment Manufacturer
 Unit 2, Trevanah Road
 Troon Industrial Park
 LE4 9LS - Leicester
uksales@sammic.com
 Tel.: +44 0116 246 1900



| | |
|----------|------|
| Project | Date |
| Item | Qty |
| Approved | |

product sheet
updated 06/03/2018