

**Huebsch is the answer.**



**25, 30 and 35 lb Loadstar™  
OPL Tumblers and 30-45 lb  
Twinstar™ OPL Stack tumblers**



 **Huebsch®**



## Huebsch is the answer.

Anybody can sell you laundry equipment and discuss the merits of each nut and bolt. However, at Huebsch, our priority is answering your questions about how working with us will make your business easier to run and more profitable.

Customers have selected Huebsch products for their ease of use, supreme durability and because owning a Huebsch product brings a service and support network that's unmatched within the industry. For profitability, reliability and ease of use, Huebsch is the answer.

## Staying a Load Ahead

**How are Huebsch LoadStar™ and TwinStar™ tumblers the answer to helping my operation stay on top of its laundry challenges?**

### **Highly efficient.**

Huebsch tumblers utilize an axial airflow process, which reduces energy consumption and produces some of the industry's fastest dry times. This innovative drying process directs all heated air through the load at the optimum time in the tumble process. Faster drying cycles reduce processing times and help your operation maximize throughput.



### **Extra capacity.**

With today's large capacity washers, it's easy for there to become backups on the drying side. Huebsch LoadStars™ are offered in 25, 30 and 35 lb models to alleviate this scenario. Even the 25 lb model boasts a spacious 7.7 cu. ft. cylinder for efficient drying of large loads, ultimately giving your operation the tools for maximum productivity.

## Quality You Can Touch

Laundry equipment is a sizable investment, how do I know Huebsch products are up to the rough demands of my on-premises laundry?

### Rugged doors.

Doors can expect to see their share of slamming, wear and tear and overall mistreatment. LoadStar™ doors are made of stainless steel to resist chipping and incorporate durable latches and hinges, to stand up to years of wear and stay looking good. You will see, feel and hear the quality every time you open or close the door.

### Rugged shells.

Huebsch electrostatically applies paint for superior bonding. A baking process then produces a hard exterior shell that's both durable and looks good.

### Staying in control.

LoadStar™ models can be configured with either a programmable micro-processor control or dual digital timer control. The micro-processor control features four preset drying cycles and offers the ability to further customize four additional programs.



Micro-processor Control



Dual Digital Control

This programmability enables you to get the results you desire every load with no wasteful overdrying. With the dual digital timer control, operators can set drying time (0-60 minutes), cool down time (0-15 minutes) and temperature (high, medium, low, no heat). Additional user-friendly features include a one-touch cycle repeat, automatic anti-wrinkle extended tumble and time remaining display.

## Easy To Own

How do LoadStar™ models make things easier on me as an owner?

### Low maintenance.

Large lint compartments mean LoadStars™ don't have to be emptied as often as other models. Huebsch's new twist latch also eliminates the need for a key, saving additional time. In addition, a heavy-duty belt delivers a long life to reduce maintenance time and costs.

## Short on Time and Space?

My laundry needs more drying capacity, but lacks the room to add equipment. How can Huebsch meet my needs?

### Stack up the drying power.

The Huebsch TwinStar45™ and TwinStar30™ stack drying tumblers deliver 90 and 60 lbs of capacity, respectively. Laundries get the benefit of having two dryers in the space of one.

### A perfect fit.

Not only do Huebsch TwinStars™ deliver superior capacity and performance, but they also fit through a 36" door, making them perfect replacement units.

# 25-35 Tumblers and 30-45 lb Stack Tumbler Specifications

Models	H0220	H0270	H0300 (STACK)	H0350	H45 (STACK)
Control Options	Programmable (OM), Electronic (QT)	Programmable (OM), Electronic (QT)	Electronic (QT)	Programmable (OM), Electronic (QT)	Electronic (QT)
Dry Weight Capacity - lb (kg)	25 (11.3)	30 (13.6)	2 x 30 (13.6)	35 (15.9)	2 x 45 (20.4)
Width - in (mm)	28" (711)	28" (711)	31 1/2" (800)	31 1/2" (800)	34 1/2" (876)
Depth - in (mm)	40 7/8" (1038)	46 7/8" (1191)	42 3/4" (1086)	46 7/8" (1191)	48 5/8" (1235)
Height - in (mm)	63 7/8" (1622)	63 7/8" (1622)	76 1/4" (1937)	63 7/8" (1622)	81 1/16" (2059)
Cylinder Depth - in (mm)	24" (610)	30" (762)	26" (660)	30" (762)	30" (762)
Cylinder Diameter - in (mm)	26 1/2" (673)	26 1/2" (673)	30" (762)	30" (762)	33" (838)
Cylinder Volume - cu. ft. (liters)	7.7 (217)	9.6 (271)	10.6 (301)	12.3 (347)	14.8 (421)
Door Opening Size - in (mm)	22 11/16" (576)	22 11/16" (576)	22 11/16" (576)	22 11/16" (576)	26 7/8" (683)
Airflow - cfm (liters/sec.)	50 Hz: 430 (203)	50 Hz: 430 (203)	50 Hz: 340 (160)	50 Hz: 550 (260)	50 Hz: 500 (236)
Energy Data	<b>Gas Models:</b> 50 Hz: 64,000 Btu/hr (18.8 kW)  <b>Steam Models:</b> At 100 psi (6.9 bar): 3.9 BHP 135,000 Btu/hr (39.6 kW)  <b>Electric Models:</b> 12 kW	<b>Gas Models:</b> 50 Hz: 73,000 Btu/hr (21.4 kW)  <b>Steam Models:</b> At 100 psi (6.9 bar): 3.9 BHP 135,000 Btu/hr (39.6 kW)  <b>Electric Models:</b> 21 kW	<b>Gas Models:</b> 50 Hz: 73,000 Btu/hr (21.4 kW) per pckt  <b>Steam Models:</b> At 100 psi (6.9 bar): 3.2 BHP 111,000 Btu/hr (32.5 kW)  <b>Electric Models:</b> 21 kW	<b>Gas Models:</b> 50 Hz: 90,000 Btu/hr (26.4 kW)  <b>Steam Models:</b> At 100 psi (6.9 bar): 3.8 BHP 166,000 Btu/hr (48.6 kW)  <b>Electric Models:</b> 24 kW	<b>Gas Models:</b> 50 Hz: 87,000 Btu/hr (25.5 kW) per pckt  <b>Steam Models:</b> N/A  <b>Electric Models:</b> N/A
Electrical Specifications					
Gas and Steam 100/200/50/1 200/50/1 230-240/50/1 200/50/3 230-240/50/3 380/400-415/50/3  Electric* 200/50/1 230-240/50/1 200/50/3 230-240/50/3 380/50/3 400-415/50/3	<b>Amps:</b> 12.1/7.5 N/A 7.5 2.9 3.5 1.5/1.6  63 58 36 33 20 18	<b>Amps:</b> 12.1/7.5 N/A 7.5 2.9 3.5 1.5/1.6  105 95 60 55 33 31	<b>Amps:</b> 24.2/15.0 total N/A 15.0 total 5.8 total 7.0 total 3.0/3.2 total  N/A N/A 120 total 110 total 66 total 62 total	<b>Amps:</b> 12.1/7.5 N/A 7.5 2.9 3.5 1.5/1.6  119 108 65 62 38 35	<b>Amps:</b> N/A 11.2 total 10.8 N/A N/A N/A N/A N/A
Plumbing Connections - in	Gas Models: 1/2" - NPT Steam Models: 3/4" - NPT	Gas Models: 1/2" - NPT Steam Models: 3/4" - NPT	Gas Models: 1/2" - NPT Steam Models: 3/4" - NPT	Gas Models: 1/2" - NPT Steam Models: 3/4" - NPT	Gas Models: 1/2" - NPT Steam Models: N/A
Shipping Dimensions Approx. - in (mm)	Width 30" (762) Depth 43" (1092) Height 69" (1753)	30" (762) 49" (1245) 69" (1753)	32 1/2" (825) 47" (1194) 81" (2057)	33" (838) 49" (1245) 69" (1753)	35 1/2" (902) 54" (1372) 85" (2159)
Net Weight - lb (kg)	299 (135)	331 (150)	544 (247)	361 (164)	673 (305)
Shipping Weight - lb (kg)	332 (151)	364 (165)	582 (264)	394 (179)	718 (326)
Agency Approvals	cCSA <sub>US</sub> , CE, CSA Star, CSA Flame	cCSA <sub>US</sub> , CE, CSA Star, CSA Flame	cCSA <sub>US</sub> , CE, CSA Star, CSA Flame	cCSA <sub>US</sub> , CE, CSA Star, CSA Flame	cCSA <sub>US</sub> , CE, CSA Star, CSA Flame

