

Counter Prep Station - Fridge Only Standard Drawers + Solid Worktop



HCS2/CW

Standard Castors (C) Solid Worktop (W)

Hydrocarbon R600a Refrigerant



A+ Energy Rating (Consumption 239 kWh/annum)

Under Counter Prep Station - Fridge Only Standard Drawers + Cover Top



HCS2/CT
Standard Castors (C)

Cover top (T)

Storage Capacity

Gastronorm (GN) Pans

4 x 1/1 GN 100 mm Deep or equivalent (per Drawer)

Maximum Weight 40 kg of Food (per Drawer)

Volume 86 Litres (per Drawer)

Applications

- Bulk storage at the point of use
- Ideal for meat, deli and larder prep
- Suitable for pastry and dessert prep
- Perfect storage for garnish and and 'mise en place' generally
- Bulk storage next to deep fry station, with worktop mounted
 Fry Basket Rack as an optional extra

Temperature Flexibility

Foods can be stored at the optimum set point anywhere in the range



Climate Testing

Tested to Climate Class 4
(30°C & 55% relative humidity)
for temperature and energy
consumption and to Climate
Class 5 (40°C & 40% relative
humidity) for temperature

Electrical

Mains Supply 230 Vac 50 Hz

Power Socket (included) Correct 2 or 3 Pin Plug fitted for each country

Mains Lead (included)


2 Metre Coiled Lead

PREP STATION - COUNTER & UNDER COUNTER - FRIDGE ONLY - SIDE ENGINE UNITS - HCS2 SERIES



Plan View |

Prep Station A+ Fridge Only (HCS2) with Open Drawer





Extended Tops

Solid Worktops (W) can be extended up to 200 mm left & right and 150 mm back, to give more preparation space


Elevation

Counter Prep Station A+ Fridge Only (HCS2) Standard Castors (C) Solid Worktop (W)





Under Counter Prep Station A+ Fridge Only (HCS2) Standard Castors (C) Cover top (T)





Tops

Double

Drawer

Module

Base



















OPTIONS (Note: due to rounding differences, the dimensions for Drawer Module + Top + Base may vary by 1 mm compared to the dimensions shown below)

Fridge Only Counter Prep Station Specifications

PREP STATION + SOLID WORKTOP (W)	High Castor Base (HC)		Standard Castor Base (C)		Small Castor Base (SC)		Rollers & Feet Base (R)		Small Rollers & Feet Base (SR)		Locking Roller Base (L)		Small Locking Roller Base (SL)	
Finished Height	971 mm	HCS2/HCW	900 mm		879 mm	HCS2/SCW	855 mm	HCS2/RW	845 mm	HCS2/SRW	855 mm	HCS2/LW	845 mm	HCS2/SLW
Load Bearing Capacity	230 kg		300 kg	HCS2/CW	300 kg		225 kg		225 kg		225 kg		225 kg	

Fridge Only Under Counter Prep Station Specifications

PREP STATION + COVER TOP (T)	High Castor Base (HC)		Standard Castor Base (C)		Small Castor Base (SC)		Rollers & Feet Base (R)		Small Rollers & Feet Base (SR)		Locking Roller Base (L)		Small Locking Roller Base (SL)	
Finished Height	962 mm	HCS2/HCT	891 mm	HCS2/CT	870 mm	HCS2/SCT	846 mm	HCS2/RT	836 mm	HCS2/SRT	846 mm	HCS2/LT	836 mm	HCS2/SLT
Load Bearing Capacity	0 kg		0 kg	HC32/C1	0 kg	HC32/3C1	0 kg		0 kg		0 kg		0 kg	