

Technical specification



HR200: 200 Ltr Undercounter Cabinet Refrigerator

13-111

Undercounter refrigerator cabinet

About the product

Convenient, practical and tough Undercounter Cabinets offer compact, on-the-spot storage.

Available to finance with our awardwinning <u>interest-free credit</u> and <u>leasing</u>

Learn more about our <u>Undercounter</u> <u>Cabinets</u>

Features and benefits

- Front breathing refrigeration system makes this model suitable for use in enclosed areas
- Front breathing, water cooled refrigeration system makes this model suitable for use in enclosed areas
- High quality magnetic door gasket
- Easy to use microprocessor control with digital display for easy visual reference
- Stainless steel exterior as standard with aluminium interior
- Supplied on roller castors as standard for ease of movement and positioning
- Operates in ambient temperatures of up to 40°C (ISO Climate Class 5)

Technical		Build	
Temperature	Refrigerator +3/+5°C	Finish ext/int	S/S & Alu
Refrigerant	R290	Number of sections	1
Electrical supply	230/50/1	Section configuration	Right hinge
Fuse rating (A)	10	System	Integral
Current (A)	1.2		
Power (W)	225		
Refrigerant mass (g)	116		

Dimensions		Energy	
Height (mm)	825	Energy grade	A +
Width (mm)	685	Climate Class	5
Depth (mm)	755	EEI	13.68
Gross volume (ltr)	200	GWP	3
Net volume (Itr)	100.2	AEC (kWh)	279.94
Leg type	Roller castors rear, levelling bolts front	Daily energy consumption (kWh)	0.77
Gross weight (kg)	62.5		
Net weight (kg)	56		

Footnotes

• For ventilation, ensure that 50mm clearance is allowed above and around the cabinet

Thank you for your interest in this product. We hope you now have everything you need to choose Foster, however if you have any further questions, please do not hesitate to contact us.

Foster Refrigerator, Oldmedow Road, King's Lynn, Norfolk, PE30 4JU +44 (0)1553 691122 | sales@foster-gamko.com | www.fosterrefrigerator.com

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.