



Page Catalog : **537-Ed8**

Ventilated refrigerator 700 liters, 1 glass door (GN 2/1), on wheels

ID70/R6G

Descriptions

mm (W x D x H)	693 x 856 x 2145
T°	0° +8°
kW	0.19
Voltage	230/1N 50HZ
gross Weight (Kg)	258 kg
Volume (m³)	2.9 m ³

Product details

- Energy efficiency class : B (Climate Class 4 “room temperature +30C° - relative humidity 55%”).
- Endowment : 3 grid GN 2/1 (530x650 mm).
- Refrigerant R600a.
- Delivered with 4 wheels, 2 with brakes.

- Made of food-grade stainless steel, with AISI 304 interior and AISI 441 exterior (gray treated steel at the back), monocoque frame
- Internal embossed side panels.
- Embossed interior bottom with rounded angles and corners (smooth surface without roughness)
- Bottom equipped with a drain plug for major maintenance.
- Doors with ergonomic (non-protruding) and reversible handle (predisposition for key lock), closure ensured by magnetic “pressure” seal (easy replacement without tools), hinges with 100° stop and door closure with automatic return
- Traditional compressor unit, ventilated condenser.
- Ventilated evaporator treated against salt and food acids "coating".
- Capillary cooler expansion.

- Digital controller : (Sealed box, waterproof), front panel with LED display “Wide”.
- Internal lighting, with switch.
- Factory-programmed defrosting cycles (modifiable as desire).
- Automatic evaporation of the condensation.
- CFC-free polyurethane insulation (80 mm).
- Device built in compliance with all applicable (CE) regulation.

The +

PLUS HIGH EFFICIENCY:

- High efficiency and low energy consumption components
- CFC-free polyurethane insulation (80 mm = super-insulated), less thermal dispersion, with the key to energy savings
- Refrigeration unit with "Buffer" under insulated, tropicalized box (Climatic class 5 "Ambient temperature +40°C - Relative humidity 40%").
- Exceptional performances, and a uniform temperature thanks to the forced channelling of the refrigerated air (100% optimized air flow), guaranteeing the good conservation of the products_backup_1_1.
- Double slide rails (allowing grating and GN containers at the same time!!!)
- Easy to operate thanks to hinges with 100° stop and door closing with automatic return
- Electronic controller (closed box, waterproof) with HACCP functions
- Comes with standard wheels, easy to move for maintenance and after-sales service.