JUICERS

J 80 Ultra



SALES FEATURES

With the J 80 Ultra, you can juice high volumes of all types of fresh fruit and vegetables in a matter of seconds.

TECHNICAL FEATURES

J 80 Ultra juicer - 230V/50/1. Power: 700 W. Constant speed: 3,000 rpm. Magnetic safety device and motor brake. Stainless-steel bowl and motor unit. Equipped with a large patented automatic feed tube (Ø 79 mm). Stainlesssteel juicer basket, grating disc and filter. Extraction rate: 120 l/h, equivalent to one glass of fresh juice every 7 s. Supplied with a large 6.5-litre pulp container, drip tray and special no-splash spout.

STANDARDS

Α

B

EN 12100-1 and 2 - 2004, EN 60204-1 - 2006, EN 1678 - 1998, EN 60529-2000: IP 55, IP 34.



640

502 457

26

378

416

467

Juice extraction rate

D

120 litres/hour

A glass of ultra-fresh juice in just 7 seconds

PRODUCT FEATURES

MOTOR BASE

E

- Induction direct drive motor for intensive use.
- Very powerful, heavy-duty motor so quiet it can be used right in front of the customer
- Power: 700 W
- Stainless-steel bowl and motor unit
- Magnetic safety device and motor brake
- Constant speed: 3,000 rpm

JUICER FUNCTION

- All-metal juicer boasting our Auto Feed system (Ø 79 mm = whole apple) for continuous throughput
- Stainless-steel juicer basket, grating disc and filter for easy cleaning and aftercare
- No-splash spout
- High clearance (162 mm), allowing a jug or cocktail glass to be placed underneath the spout
- You can produce up to 135 glasses of juice before having to stop and empty the large-capacity pulp container

C TECHNICAL DATA		
Power	700 Watts	
Electrical datas	Single phase - plug supplied	
Constant speed	3,000 rpm	
Dimensions (LxWxH)	235 x 535 x 502 mm	
Gross weight	12.5 kg	
Supply	Amperage	Reference
230∨/50/1		56000A
230V/50/1 UK plug		56001A
230V/50/1 DK		56007A
120V/60/1		56005A
220V/60/1		56004A

500





J 80 Ultro

Specification sheet

www.robot-coupe.com

Update: June 2014

450

23

robot Ø coupe°