

ECO MIDI K 82 CCG 4S



With an energy consumption of only 327 kWh/year (Energy test Ecodesign) the ECO MIDI 82 refrigerator already now ranks in energy class A.

The Ecodesign test method records the 24 hour energy consumption and multiplies it by 365 to get the annual energy consumption (AEC). The 24 hour consumption is calculated from 2 test periods of 12 hours each. The first period has sequences of door openings while the second is a stabilization period with closed door.

ECO MIDI 82 cabinets combine stylish design with high functionality and low energy consumption.

- The controls are concealed behind the top panel, protected against splashing water.
- Design principle of "no broken surfaces" makes the cabinets easy to clean.
- The distinctive aluminum profiles stretching from top to bottom on both sides of the cabinet impart strength and enhance appearance.
- The modular rails can go directly in the dishwasher.
- Easy access to stored items as the storage compartment is raised 37 cm above the floor.

ECO MID 82 is suitable for the 2/1 GN wide GN system where two 1/1 GN pans can be placed side by side on each shelf.

TECHNICAL INFORMATION

| | |
|---------------------------------|--|
| Varenummer | 962820011 |
| Category | Storage Cabinets |
| Type | Refrigerator |
| Line | 2/1 GN wide |
| Series | ECO MIDI |
| Equipped with | Right hand hinged reversible door, automatic door closing, 4 stainless shelves, LED lighting |
| Temperature range | +2/+12°C |
| Volume, gross | 603 ltr. |
| Net usable volume | 459 ltr. |
| Exterior/Interior | Stainless/Stainless |
| Dim. W x D x H, mm | 820 x 771 x 2000 |
| Weight, packed | 137 kg |
| Refrigerant / GWP | R 290 (propane)/0.11 kg/CO2e 0.37 kg/3 |
| Ref.capacity at -10° | 333 Watt |
| Connection | 230V, 50 Hz |
| Connection load | 224 Watt |
| Energy Efficiency Class | A |
| Energy consumption / year (AEC) | 327 kWh |
| Sound level | 48.1 dB(A) |

