

# **MODEL: LGR2**



The perfect Full English Breakfast has never been this quick and simple. Introducing the 3kW Lynx 400 Griddle - offering incredible versatility, it's ideal for cooking eggs, bacon and much more besides. Compact but sturdy, the griddle is designed to plug in and play, so you'll be delivering delicious dishes in no time at all. The plate heats up fast and features an efficient heat distribution system which allows you to use the whole surface area. Perfect for cafes and pubs, the griddle is thermostatically controlled for even cooking results and comes with a splash guard to keep surround area cleaner during cooking.



#### **PRODUCT FEATURES**

- Excellent even heat distribution allows you to use the whole plate maximum output from limited counter space
- Fast heat up from cold
- One piece cast iron griddle plate with integral splashguard gives excellent heat retention
- Even heat distribution over the cooking surface which allows you to use the whole surface area
- Splash guard to keep surround area cleaner during cooking
- Thermostatically controlled for even cooking results
- Plug and play for an easy installation









# **MODEL: LGR2**

WEIGHTS & DIMENSIONS	
Width	615 mil
Depth	400 mil
Height	163 mil
Weight	21.2 kg

SHIPPING DETAILS	
Ship Width	74 cm
Ship Depth	52.5 cm
Ship Height	24 cm
Ship Weight	23.32 kg
Number of Shipment Parcels	1
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No
Returnable Item	No

## **PRODUCT CERTIFICATIONS**



ENERGY SPECS	
Primary Energy Source Type	Electricity
Electrical Amps	13
Electrical Voltage	230 volts
Electrical Watts	3000
Electrical Phase	Single
Kilowatts	3 kW

Number of Electrical Conductor Wires	1
Electrical Connection Type	Cord and Plug
Electrical Plug Type	UK 3-Pin Plug
Number of Electrical Plugs	1
Dedicated Circuit Required	No
Energy Saving	No

ADDITIONAL SPECIFICATIONS	
Control Type	Rotary Control Knob
Cooking Area Plate Depth	310 mm
Cooking Area Plate Width	590 mm
Cooking Plate Finish Material Type	Cast Iron Plate
Food Production Rate	196 x 115g [4oz] burg- ers [frozen] per hour
Legs or Casters	Not Applicable
Lower Platen Surface Type (multi-select)	Smooth

Number Of Controls	1
Number of Heating Zones	1
Plate Shape	Rectangle
Plate Thickness	6 mm
Temperature Maximum	250 °C
Temperature Minimum	50 °C
Thermostat Element Location	<b>Under Plate Mount</b>

Lincat reserves the right to modify specifications or discontinue models without incurring obligation. Dimensions nominal.

Document Auto-Generated January 23, 2024







**MODEL: LGR2** 


#### **BIDDING SPECIFICATIONS**

Bidding Specifications Not Available.

### **TECHNICAL DRAWING**







Lincat reserves the right to modify specifications or discontinue models without incurring obligation. Dimensions nominal.

Document Auto-Generated January 23, 2024