

Pizza Ovens – Premium Range

Key Features

- Type: Electric
- Counter top unit
- Firebrick base for crisp cooking
- Thermostatic temperature control to upper elements (80-480°C)
- Energy regulator temperature control to lower elements
- Timer (20 min)
- Height adjustable feet
- Internal light
- Glass viewing window



PO430-2

Construction

- Body: stainless steel grade 430
- Handles: plastic (black)
- Liner: stainless steel grade 430

Available Options


- Single oven units (PO425, PO430 and PO630)
- Double oven units (PO425-2, PO430-2 and PO630-2)

Available Accessories

- PO425/FS, PO430/FS, PO630/FS – Floor stands for single and twin deck ovens
- PO425/SK, PO430/SK and PO630/SK – Stacking kit for stacking two single deck ovens

Specifications

Model	PO425	PO425-2	PO430	PO430-2	PO630	PO630-2
External height (mm)	374	674	374	674	374	674
External width (mm)	886	886	966	966	1286	1286
External depth (mm)	902	902	1002	1002	1002	1002
Usable oven area w x d (mm) Per deck	540 x 540	540 x 540	620 x 620	620 x 620	940 x 620	940 x 620
Net weight unpacked (kg)	58	101	77	135	104	181
Gross weight packed (kg)	80	123	98	156	131	208
Shipping volume (m ³)	0.493	0.800	0.587	0.940	0.764	1.222
Total power rating (kW)	3.0	6.0	4.2	8.4	7.2	14.4
Electrical supply 1N~+E 230V 50-60Hz Current Rating (A)	13	26	18.3	36.6	31.3	N/A
Electrical supply 3N~+E 400V 50-60Hz Current Rating (A)	N/A	8.7,8.7,8.7	6.1,6.1,6.1	12.2,12.2,12.2	10.4,10.4,10.4	20.8,20.8,20.8



Lincat Limited, Whisby Road,
Lincoln LN6 3QZ,
United Kingdom

UK Sales Tel: 01522 875500 UK Spares Tel: 01522 875510 UK General Tel: 01522 875555
 UK Fax: 01522 875530 International Sales Tel: +44 1522 503250 International Fax: +44 1522 875530
 Website: www.lincat.co.uk UK Sales e-mail: sales@lincat.co.uk International Sales e-mail: export@lincat.co.uk



Document ref:
PREMIUMFZZAOVEN
S