



UTENSIL WASHER LU-75

780 x 700 mm. basket



WARE WASHING
POT WASHERS



SPECIFICATIONS

- Basket dimensions: 780 mm x 700 mm
- Stainless steel basket : 1
- Equipment: supplementary trays: 1
- Maximum glass height: 650 mm
- Cycles: 3
- Cycle duration: 120 " / 240 " / 360 "
- Production baskets/hour: 30 / 15 / 10
- Pressure pump power: 470 W

Loading

- ✓ Pump: 3,2 Hp / 2400 W
- ✓ Tank: 6000 W
- ✓ Boiler: 10500 W
- ✓ Total loading: 12900 W
- Temperature: 10 °C - 60 °C
- Wash temperature: 40 °C - 70 °C
- Rinse temperature: 70 °C - 95 °C
- Wash tank capacity: 80 l
- Boiler capacity: 12 l
- Water consumption/cycle: 6 l
- Drainage base maximum height: 185 mm
- Drain diameter: 30 mm

External dimensions (WxDxH)

- ✓ Width: 922 mm
- ✓ Depth (closed): 932 mm
- ✓ Depth (open): 1312 mm
- ✓ Height (closed): 1840 mm
- ✓ Height (open): 2035 mm
- Net weight: 196 Kg
- Noise level (1m.): 76 dB(A)

AVAILABLE MODELS

1300580 Utensil washer LU-75 230-400/50/3N

1300584 Utensil washer LU-75B 230-400/50/3N (with drain pump)

* Ask for special versions availability

SALES DESCRIPTION

Max. loading height: 650mm.

Ideal to wash big sized pots and wares.

- ✓ Powerful and high pressure: specially indicated for restaurants, ice-cream shops, pastries and butcheries.
- ✓ Constructed from stainless steel.
- ✓ Door divided in two parts, perfectly counterbalanced, easy to handle.
- ✓ Double skinned machines: silent working and reduced thermal dispersions.
- ✓ Wash tank without corners to avoid dirt accumulation in angles.
- ✓ Stamped wash dispersers in stainless steel tubes.
- ✓ Easy to remove wash- and rinse dispersers.
- ✓ Safety micro switch at the door and electronic safety device to guarantee washing temperature and time.
- ✓ Electronic control panel with LED showing wash and rinse temperature.
- ✓ Drain pump and non-return valve.

INCLUDES

- ✓ 1 stainless steel basket and insert for 4 trays.



www.sammic.co.uk

Food Service Equipment Manufacturer
 Unit 2, Trevanah Road
 Troon Industrial Park
 LE4 9LS - Leicester
uksales@sammic.com
 Tel.: +44 0116 246 1900



Project	Date
Item	Qty
Approved	

product sheet
updated 06/03/2018