

Lynx

Designed with and for the most demanding chefs. Standard equipped with Henkelman's Advanced Control System, including a 20-program memory, full colour screen and a wide variety of functions. The Lynx table-top models are HACCP compliant and compatible with a direct thermal label printer. Experience all that a vacuum packaging machine can offer, and more. . .




Lynx



“Henkelman’s Lynx series definitely bring more tools to your kitchen.”

LYNX 32




PUMP CAPACITY 8 m³/h
MACHINE CYCLE 15–30 sec
CHAMBER DIMENSIONS
360 x 320 x 103 mm
MACHINE DIMENSIONS
530 x 390 x 380 mm
SEAL BAR 320 mm
WEIGHT 43 kg
VOLTAGE 230V-1-50HZ
POWER 0,5 kW

STANDARD
SENSOR CONTROL, ACS,
DOUBLE/CUT-OFF/WIDE SEAL
(8 MM), SOFT AIR

OPTIONS
LIQUID CONTROL, GAS FLUSH,
HIGH TEMP, 1-2 CUT-OFF SEAL

LYNX 42



Standard with ACS. Optional: label printer

PUMP CAPACITY 16 m³/h
MACHINE CYCLE 15–30 sec
CHAMBER DIMENSIONS
360 x 420 x 115 mm
MACHINE DIMENSIONS
530 x 490 x 395 mm
SEAL BAR 420 mm
WEIGHT 55 kg
VOLTAGE 230V-1-50Hz
POWER 0,7 kW

STANDARD
SENSOR CONTROL, ACS,
DOUBLE/CUT-OFF/WIDE SEAL
(8 MM), SOFT AIR

OPTIONS
LIQUID CONTROL, GAS FLUSH,
HIGH TEMP, 1-2 CUT-OFF SEAL

The chamber dimensions listed refer to the usable space in the vacuum chamber (length x width x height). The machine dimensions listed refer to length x width x height. Other voltages available. Textual and printing errors reserved.